Date: 11/04/2023

MABXXUN - -30...30 mbar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F

Diaphragm pressure switch

Item number: 48769572

Quantity: 1 pcs.

Order code: MABXXUN-MCBSC-2AMZZZZ1ZZZZZZZZZZZZZZZZZZZZ ZCK1BW
M001700IZZZZZZZZ
F4-C5- - - - -

Overview:
MABXXUN - -30...30 mbar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F
Diaphragm pressure switch
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 1x SPDT silver contact
setting range: -30...30 mbar
Standard, working range = -30...30 mbar, proof pressure -60/250 mbar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point customer-specifically configured
1. set point: 17.00 mbar increasing,

Details:
Diaphragm pressure switch
Flameproof enclosure Ex d
Model MA
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span
Contact version: 1x SPDT silver contact
setting range: -30...30 mbar
working range: Standard, working range = -30...30 mbar, proof pressure -60/250 mbar
Set Point customer-specifically configured
Unit: mbar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66

© 2023 - WIKA Instruments s.a.r.l.

MABXXUN
Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel AISI 316L
1. set point: 17.00 mbar increasing,

© 2023 - WIKA Instruments s.a.r.l.