DATASHEET - 32AMP 440V AC OFFSET BLADE TAG BS88 FUSE



Fuse-link, low voltage, 32 A, AC 440 V, 80 kA, BS88/F3, 27 x 80 mm, gL/gG, BS

Powering Business Worldwide

Part no.	**32Amp 440V ac OFFSET BLADE TAG BS88 FUSE**
Catalog No.	**XS32**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	32
Rated voltage			AC 440 V
Construction size			BS88/F3
Size			27 x 80 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			offset bladed tags
Standards/Regulations			BS88-2 IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	32
Rated voltage		V	440
Voltage type			AC
Rated switching capacity		kA	80
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

© 02/2021 by Eaton Industries GmbH