DATASHEET - FAZ-XAA-NA110-415VAC

Shunt release, up to 40A, 110-415V, 1HP

Part no. **FAZ-XAA-NA110-415VAC**
102036

Powering Business Worldwide

General specifications

Product name	Eaton Distribution parts
Part no.	FAZ-XAA-NA110-415VAC
EAN	4015081019274
Product Length/Depth	105 millimetre
Product height	75.5 millimetre
Product width	17.7 millimetre
Product weight	0.11 kilogram
Compliances	RoHS conform
Certifications	CSA (File No. 204453) UL (File No. E257181) UL 489 IEC/EN 60898 CSA-C22.2 No. 5-09 North America (UL listed, CSA certified) UL (Category Control Number DIHS, DIHS7) CSA (Class No. 1437-01) CE marking IEC 61373 EN45545-2
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes

Product Specification Details

Accessory/spare part type	Shunt release
Additional equipment required	Shunt release (for power circuit breaker)
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for 110-V systems
Assembly width	1
Degree of protection	IP20 (IEC) IP40 UL/CSA Type: -
Device fitting	Miniature circuit breaker (MCB)
Enclosure width	105 mm
Frame	Standard front dimension: 45 mm
Frequency rating	50 Hz / 60 Hz
Functions	Shunt release (for power circuit breaker)
Mounting width	17.5 mm (1 space unit)
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	1
Number of switches (fault signal)	0
Rated operational voltage (Ue) - max	415 V
Rated switch current	0 A
Suitable for current of main contact unit - max	0 A
Terminal protection	Busbar tag shroud to BGV A3
Terminal type	Twin-purpose terminals
Type	Accessory Accessory for miniature circuit breaker

Used with			Shunt releases Accessory for miniature circuit breaker Accessory
Voltage range			110 V AC - 415 V AC
Voltage type			AC/DC

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])

Device fitting			Miniature circuit breaker (MCB)
Additional equipment			Shunt release (for power circuit breaker)
Installed at the factory			No
Width in number of modular spacings			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	415
Voltage type for actuating			AC/DC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	0

© 04/2023 by Eaton Industries GmbH