

Cable trunking SES®
with slots and base punching


GN-A6/4 LF

Material:	Rigid PVC quality 9051 LF
Colour:	grey RAL7030
Operating temperatures:	-5 to +65°C
Density:	1,56
Volume resistivity:	10^{15} Ω.cm
Dielectric strength:	15kV/mm
Spécification:	V0 UL94 DIN 5510-2 S3, SR1, ST2
Standard length:	2 meters
Double sided adhesive:	upon request
Minimum delivery:	1 complete packing (with lids)




type	trunking art. no.	m	outside dim. H mm	outside dim. W mm	cables per trunking (filling 50 %) 1 mm²	1,5 mm²	2,5 mm²	lids (alone) art. no.	m
GN-A6/4 30x 25	0839 0131 013	60	30	25	37	31	26	0839 0500 013	48
GN-A6/4 30x 40	0839 0132 013	36	30	40	68	56	47	0839 0510 013	24
GN-A6/4 40x 25	0839 0141 013	48	40	25	52	43	36	0839 0500 013	48
GN-A6/4 40x 40	0839 0142 013	32	40	40	94	77	64	0839 0510 013	24
GN-A6/4 40x 60	0839 0143 013	24	40	60	149	122	102	0839 0520 013	24
GN-A6/4 40x 80	0839 0144 013	24	40	80	204	168	140	0839 0530 013	24
GN-A6/4 40x100	0839 0145 013	12	40	100	259	213	178	0839 0540 013	12
GN-A6/4 60x 25	0839 0151 013	48	60	25	80	66	55	0839 0500 013	48
GN-A6/4 60x 40	0839 0152 013	32	60	40	144	118	99	0839 0510 013	24
GN-A6/4 60x 60	0839 0153 013	24	60	60	229	188	157	0839 0520 013	24
GN-A6/4 60x 80	0839 0154 013	16	60	80	313	257	215	0839 0530 013	24
GN-A6/4 60x100	0839 0155 013	16	60	100	398	327	273	0839 0540 013	12
GN-A6/4 60x120	0839 0156 013	12	60	120	483	397	332	0839 0550 013	12
GN-A6/4 80x 25	0839 0161 013	24	80	25	107	88	74	0839 0500 013	48
GN-A6/4 80x 40	0839 0162 013	24	80	40	193	159	133	0839 0510 013	24
GN-A6/4 80x 60	0839 0163 013	24	80	60	308	253	211	0839 0520 013	24
GN-A6/4 80x 80	0839 0164 013	16	80	80	422	347	290	0839 0530 013	24
GN-A6/4 80x100	0839 0165 013	12	80	100	537	441	369	0839 0540 013	12
GN-A6/4 80x120	0839 0166 013	16	80	120	652	535	447	0839 0550 013	16
GN-A6/4 100x 40	0839 0171 013	24	100	40	240	198	165	0839 0510 013	24
GN-A6/4 100x 60	0839 0172 013	16	100	60	384	316	264	0839 0520 013	24
GN-A6/4 100x 80	0839 0173 013	16	100	80	529	435	363	0839 0530 013	24
GN-A6/4 100x100	0839 0174 013	16	100	100	673	553	462	0839 0540 013	12




C3/1-01



C3/1-01



C3/1-02



C3/1-02


C3/5-01

C3/5-02



C3/6-01



C3/6-01



D4/6-01



GN-A6/4 LF


H = 30 mm
H = 40 mm
H = 60 mm
H = 80 mm
H = 100 mm













W = 25, 40 and 60 mm



W = 80, 100 and 120 mm



Base punching to NF EN 50085

H (mm)	30	40	60	80	100
h1 (mm)	5	7	9	11	16