DATASHEET - M22-WRS-MS5

Key-operated actuator, maintained, 2 positions, MS5, Key withdrawable: 0, I, Bezel: titanium

Part no. **M22-WRS-MS5**
111785

Product name	Eaton Moeller® series M22 Key-operated actuator
Part no.	M22-WRS-MS5
EAN	4015081113354
Product Length/Depth	70 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.034 kilogram
Compliances	CE Marked
Certifications	IEC 60947-5 CSA Std. C22.2 No. 14-05 CSA Std. C22.2 No. 94-91 UL 508 EN 60947-5 VDE VDE 0660 CSA-C22.2 No. 94-91 UL CSA IEC/EN 60947-5 CSA File No.: 012528 IEC/EN 60947 CSA Class No.: 3211-03 CE UL File No.: E29184 CSA-C22.2 No. 14-05 UL Category Control No.: NKCR
Product Tradename	M22
Product Type	Key-operated actuator
Product Sub Type	None
Catalog Notes	Key withdraw convertible with coding adapters M22-XC-... Not suitable for master key systems
Bezel color	Titanium
Bezel material	Plastic
Color	Black
Design	Key operated
Fitted with:	Front ring
Functions	Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
Key code	MS5
Accessories	1 key included with supplied equipment.
Degree of protection	NEMA 4X, 13
Degree of protection (front side)	IP66
Lifespan, mechanical	100,000 Operations
Opening diameter	22.5 mm
Operating frequency	100 Operations/h
Operating torque	0.5 N·m
Product category	RMQ-Titan
Switching angle	60 °
Type	Key-operated button
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Connection to SmartWire-DT			With SWD-RMQ connections Yes
Actuator color			Black
Actuator function			Switching function latching Key withdrawable in position 1 Maintained Key withdrawable in position 0
Actuator type			Key
Number of switch positions			2
Force for positive opening - min			0 N
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdiss			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss10.0.1-27-37-12-13 [AKF031014])

Number of switch positions			2
Type of control element			Key
Suitable for illumination			No
Colour control element			Black
Colour indicator light cap			Other
Construction type lens			Round
Hole diameter		mm	22.5

Width opening		mm	0
Height opening		mm	0
Switching function latching			Yes
Spring-return			No
With front ring			Yes
Material front ring			Plastic
Colour front ring			Titanium
Degree of protection (IP), front side			IP66
Degree of protection (NEMA)			4X, 13

© 04/2023 by Eaton Industries GmbH