Date: 12/04/2023

RLS-1000; Guide tube length: 430.0; 1 switching output

RLS-1000; Guide tube length: 430.0; 1 switching output

Item number:	48793889
Quantity:	1 pcs.
Order code:	RLS-10003M100500ZZZZZZZZZZZZZZZZZZZ1AZ8M043004ZC Z1W101ARS1ZL4
Overview:	RLS-1000; Guide tube length: 430.0; 1 switching output Magnetic float switch, Stainless steel version Model RLS-1000 Output Signal: 1 switching output Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 50.0 Electrical connection: Aluminium housing standard (75x80x57 mm), IP66 pin assignment el. connection: see product label Process connection: G 1, installation from outside Guide tube length: 430.0 mm medium temperature: -30 °C ... 80 °C Wetted parts: Stainless steel 1.4571 Float: Cylindrical float Ø 22 mm, 1.4571, PN16 Specifications according to data sheet: LM 50.03
Details:	RLS-1000; Guide tube length: 430.0; 1 switching output Magnetic float switch, Stainless steel version Model RLS-1000 Output Signal: 1 switching output Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 50.0 Electrical connection: Aluminium housing standard (75x80x57 mm), IP66 pin assignment el. connection: see product label Process connection: G 1, installation from outside Guide tube length: 430.0 mm medium temperature: -30 °C ... 80 °C Wetted parts: Stainless steel 1.4571 Float: Cylindrical float Ø 22 mm, 1.4571, PN16 Specifications according to data sheet: LM 50.03

© 2023 - WIKA Instruments s.a.r.l.