Date: 22/01/2024

PSM-520; -0.4 ... +7 bar; G 1/4 B

PSM-520; -0.4 ... +7 bar; G 1/4 B

Item number: 14269089

Quantity: 1 pcs.

Order code: PSM-520-B -1-GBL-Z W101AP521 52

Overview:

PSM-520; -0.4 ... +7 bar; G 1/4 B
Pressure switch, heavy-duty version
Specifications according to data sheet: PV 35.01
Switching function: Changeover SPDT
Setting of switching point: Factory setting
Rising pressure: switch point 3 bar, reset point 2 bar, switch differential 1 bar
Wetted parts: Copper alloy, free cutting steel tin-plated
Additional ordering information: without
Non-repeatability: ≤ 2 % of span
Measuring principle: Bellows
Electrical connection: Rubber grommet for cables □6 ... 14 mm (□0.24 ... 0.55 in)
Electrical rating: AC-1: 10 A, AC 230 V resistive load AC-15: 6 A, AC 230 V inductive load
Permissible medium temperature: -20 … +100 °C / -4 … +212 °F

Details:

PSM-520; -0.4 ... +7 bar; G 1/4 B
Pressure switch, heavy-duty version
Specifications according to data sheet: PV 35.01
Switching function: Changeover SPDT
Setting of switching point: Factory setting
Rising pressure: switch point 3 bar, reset point 2 bar, switch differential 1 bar
Wetted parts: Copper alloy, free cutting steel tin-plated
Additional ordering information: without
Non-repeatability: ≤ 2 % of span
Measuring principle: Bellows
Electrical connection: Rubber grommet for cables □6 ... 14 mm (□0.24 ... 0.55 in)
Electrical rating: AC-1: 10 A, AC 230 V resistive load AC-15: 6 A, AC 230 V inductive load
Permissible medium temperature: -20 … +100 °C / -4 … +212 °F

© 2024 - WIKA Instruments s.a.r.l.