pulse operated latching relays

NEW


4 124 01


4 124 12


0 491 20


4 124 29


4 124 36

Dimensions **see e-catalogue**

Noiseless pulse operated latching relay

Conform to standard EN 60669-2-2

Single pole - 16 A - 250 V~

Pack	Cat.Nos	Control voltage	Type of contact	Connection	Number of modules
1	4 124 00	230 V	1 N/O		1

Delayed noiseless pulse operated latching relay

Conform to standard EN 60669-2-2

Single pole - 16 A - 250 V~

Pack	Cat.Nos	Control voltage	Type of contact	Connection	Number of modules
1	4 124 01	230 V	1 N/O		1

Standard pulse operated latching relays

Conform to standard EN 60669-2-2
Maximum 2 auxiliary devices per latching relay

Single pole - 16 A - 250 V~

Pack	Cat.Nos	Control voltage	Type of contact	Connection	Number of modules
1	4 124 04	12 V	1 N/O		1
1	4 124 05	24 V	1 N/O		1
10	4 124 08	230 V	1 N/O		1

2-pole - 16 A - 250 V~

1	4 124 10	24 V	2 N/O		1
1	4 124 11	48 V	2 N/O		1
1	4 124 12	230 V	2 N/O		1

4-pole - 16 A - 250 V~

Can be used for 3-pole assembly

1	4 124 14	24 V	4 N/O		2
1	4 124 16	230 V	4 N/O		2

Surface mounting pulse operated latching relays

10 A - 230 V~ - 50/60 Hz
Suitable for new installations or retrofitting of existing ones
Compatible with electronic ballasts and fluocompact lamps
Mounting on plate or in flush-mounting boxes Ø 67 mm
Equipped with automatic terminals for flexible or rigid wires (max. 2.5 mm)
Power : min. 7 W / max. 2300 W
IP 20 - IK 04
Dimensions: 49 x 46 x 26 mm
Maximum current when used with illuminated push-buttons : 50 mA

Noiseless

Pack	Cat.Nos	
10	0 491 20	Single pole
10	0 491 21	Single pole with timer Enables energy savings by switching off lighting after a specified period Time delay adjustment from 1 to 60 min. Switch-off pre-warning function (can be disabled)

Signalling auxiliary

Fitted on left-hand side of latching relay (equipped or not with control auxiliary)
Maximum 2 auxiliaries per latching relay
Used to signal the status of the contacts on the associated product

Auxiliary changeover switch

Pack	Cat.Nos	I max.	Voltage	Contact	Number of modules
1	4 124 29	5 A	250 V~	N/C + N/O	0.5

Control auxiliary

Fitted on left-hand side of latching relay
Maximum 1 control auxiliary per latching relay
Compatible with signalling auxiliary Cat.No 4 124 29

Auxiliary device for centralized control

For a centralized control of different latching relays from one single point

Pack	Cat.Nos		Number of modules
1	4 124 33	For latching relays 24 V~ to 48 V~	0.5
1	4 124 34	For latching relays 230 V~	0.5

Auxiliary device for general centralized control

1	4 124 36	For simultanous control of different groups of latching relays, already fitted with auxiliary device for centralised control 230 V~ Cat.No 4 124 34	1

Auxiliary device for maintained contact

1	4 124 37	Allows the control of a latching relay via one maintained contact (i.e. time switches)	0.5

Compensator module

Used to control 230 V~ - 50 Hz pulse operated latching relays via illuminated push-buttons without malfunctions
Connects to the terminals of the pulse operated latching relay coil
Compensation:
- 1 compensator module for a total consumption of 3 to 6 mA (example: 6 to 11 illuminated push-buttons consuming 0.55 mA each)
- 2 compensators modules for a total consumption of 6 to 9 mA (example: 12 to 17 illuminated push-buttons with consuming 0.5 mA each)

Pack	Cat.Nos		Number of modules
1	4 124 39	Impedance compensator for 230 V~ pulse operated latching relays	1

Red catalogue numbers: New products