Specifications

Eaton 9701-6101-00P

Catalog Number: 9701-6101-00P

Eaton DG1 Variable frequency drive, 230 V AC, 3-phase, 211 A, 55 kW, IP54/NEMA12, Brake chopper, DC link choke



General specifications

Product Name
Eaton DG1 variable frequency drive

Catalog Number
9701-6101-00P

EAN
4015081805860

Product Length/Depth
371 mm

Product Height
1035 mm

Product Width
486 mm

Product Weight
109 kg

Certifications
CUL
UL report applies to both US and Canada
CSA-C22.2 No. 274-13
UkrSEPRO
Specification for general requirements: IEC/EN 61800-2
UL508
C-Tick
EAC
IEC/EN61800-5
RoHS, ISO 9001
Safety requirements: IEC/EN 61800-5
UL Category Control No.: NMMS, NMMS7
CE
Certified by UL for use in Canada
IEC/EN61800-3
IEC/EN 61800-3
UL
UL File No.: E134360

Powering Business Worldwide

Catalog Notes

Features & Functions

Features

Temperature-controlled fan

Externally accessible fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl

Functions

4-quadrant operation possible

General

Air volume capacity

739 m³/h

Cable length

`C2 ≤ 10 m, Radio interference level, maximum motor cable length`

200 m, screened, maximum permissible, Motor feeder

`C3 ≤ 50 m, Radio interference level, maximum motor cable length`

Degree of protection

IP54

NEMA 12

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Fitted with:

Additional PCB protection

Brake chopper

Multi-line graphic display

PC connection

Radio interference suppression filter

Control unit

Breaking resistance

Internal DC link

IGBT inverter

DC link choke

Frame size

FS6

Mounting position

Vertical

Number of slots

2 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C1: with external filter, for conducted emissions only
C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Safety function/level

STO (Safe Torque Off, SIL1, PLc Cat 1)

Shock resistance

Storage and transportation: maximum 15 g, 11 ms (inside the packaging)
UPS drop test (for weights inside the UPS frame)
Mechanical, According to EN 61800-5-1, IEC/EN 60068-2-27

Suitable for

Branch circuits, (UL/CSA)

Vibration

Resistance: 15.8 – 150 Hz, 1 g, Maximum acceleration amplitude
Resistance: 5 - 15.8 Hz, Amplitude 1 mm (peak)
Resistance: 5 - 150 Hz, According to EN 61800-5-1, IEC/EN 60068-2-6

Climatic environmental conditions

Altitude

Max. 3000 m
Above 1000 m with 1 % derating per 100 m
Max. 1000 m
Max. 2000 m for Corner Grounded TN Systems

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient operating temperature at 150% overload - min

-30 °C

Ambient operating temperature at 150% overload - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Efficiency

97.5 % (η)

Heat dissipation at current/speed

1081 W at 50% current and 50% speed
1174 W at 50% current and 90% speed
1576 W at 100% current and 0% speed
1910 W at 50% current and 0% speed
2140 W at 100% current and 90% speed
732 W at 25% current and 0% speed
809 W at 25% current and 50% speed
952 W at 100% current and 50% speed

Input current ILN at 110% overload

242.8 A

Input current ILN at 150% overload

195.2 A

Leakage current at ground IPE - max

7.2 mA

Mains current distortion

26 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Mains voltage - min

208 V

Mains voltage - max

240 V

Operating mode

U/f control

Speed control with slip compensation

Torque regulation

Sensorless vector control (SLV)

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

240 V AC, 3-phase

230 V AC, 3-phase

Overload current IL at 110% overload

287.1 A

Overload current IL at 150% overload

316.5 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

261 A

Motor rating

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

192 A

Assigned motor current IM at 230 V, 50 Hz, 110% overload

233 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

173 A

Assigned motor current IM at 230 V, 60 Hz, 110% overload

248 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

75 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase, 110 % overload

100 HP

Apparent power

Apparent power at 230 V

104 kVA

Apparent power at 240 V

108.5 kVA

Braking function

Braking resistance

1.4 Ω

Braking torque

Max. 30 % MN, Standard - Main circuit

Adjustable to 150 %, DC - Main circuit

Adjustable to 150 % (I/Ie), DC - Main circuit

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Switch-on threshold for the braking transistor

425 VDC

Control circuit

Number of inputs (analog)

2

Rated operational current (Ie) at 150% overload

211 A

Rated operational power at 220/230 V, 50 Hz, 1-phase

55 kW

Rated operational power at 220/230 V, 50 Hz, 3-phase, 110% overload

75 kW

Rated operational voltage

240 V AC, 3-phase

230 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

400 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

2 kHz, 1 - 10 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

240 VAC

Number of inputs (digital)

8

Number of outputs (analog)

2

Number of outputs (digital)

1

Number of relay outputs

3 (parameterizable, 2 changeover contacts and 1 N/O, 6 A (240 V AC) / 6 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA options incl.)

Communication

Communication interface

DeviceNet, optional

SmartWire-DT, optional

CANopen®, optional

Modbus TCP, built in

BACnet MS/TP, built in

PROFIBUS, optional

Modbus RTU, built in

Ethernet IP, built in

Connection to SmartWire-DT

Yes

In conjunction with DXG-NET-SWD SmartWire DT module

Protocol

MODBUS

Other bus systems

TCP/IP

BACnet

PROFIBUS

CAN

PROFINET IO

DeviceNet

EtherNet/IP

Design verification

Equipment heat dissipation, current-dependent Pvid

2191 W

Heat dissipation capacity Pdiss

Resources

Application notes

PID controller

Smoke Mode and fire mode

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

211 A

Static heat dissipation, non-current-dependent Pvs

59.17 W

Heat dissipation details

Operation (with 150 % overload), allow for derating

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Analog I/Os

Torque control

Real time clock and use of the timers

Electromagnetic compatibility (EMC)

Digital I/Os

Connecting drives to generator supplies

Operating at low temperatures

Motor data and V/f curves

DG1 in pump and fan applications

Starting, stopping and operation

Dual Rating What exactly does that mean?

Load balancing in multi motor applications

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004620.pdf

DA-DC-00004676

eCAD model

DA-CE-ETN.DG1-32211FB-C54C

Manuals and user guides

MN040002_EN

mCAD model

DA-CD-dg1_fs6_mit

DA-CS-icpd_dg1_fr6_mit

Multimedia

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

Power XL General Purpose Drives

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.