View product details on medias

30.01.2025, 12:41:00 IST

SCHAEFFLER




# ARCALUB-C1-60-REFILLABLE

Automatic lubricator CONCEPT

CONCEPT1, Single-point lubricator (125 cm³, empty)

## Technical information




### Your current product variant

| | | |
|---|---|---|
| Drive System | HG | Hydrogen gas development cell |
| Lubricant volume | V60 | 60 cm³ |

### Technical data

| | | |
|---|---|---|
| | Gas drive | Functional principle |
| $V_{Lub}$ | 60 cm³ | Lubricant volume |
| $p_{op}$ | 5 bar | Operating pressure, max. |
| | ≤ NLGI 2 (suitability test required) | Lubricant |
| $n_{out}$ | 1 | Number of outlets |
| | 1 | Number of lubrication points: direct |
| $U_{op}$ | — | Operating voltage |
| | IP68 | Protection class |
| | Polyethylenterephthalat (PET) | Housing material |
| $t_{min}$ | -20 °C | Operating temperature, min. |
| $t_{max}$ | 55 °C | Operating temperature, max. |
| | arbitrary | Mounting position |
| | G¼ | Connection thread |
| | 79 x 53 x 53 | Dimensions (mm) |
| ≈m | 66 g | Weight |

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website