Specifications

Eaton 267413

Catalog Number: 267413

Eaton XIOC Digital output module for XC100/200, 24 V DC, 32DO(T)



General specifications

Product Name
Eaton XIOC Output module

Catalog Number
267413

EAN
4015082674137

Product Length/Depth
100 mm

Product Height
95 mm

Product Width
30 mm

Product Weight
0.155 kg

Certifications
CE
CSA Class No.: 2252-01
CSA File No.: 012528
UL File No.: E135462
UL508
CSA-C22.2 No. 0-M
CSA-C22.2 No. 142-M
UL Category Control No.: NRAQ
IEC/EN 61131-2
UL
EN 50178
CSA

Powering Business Worldwide

Features & Functions

Electric connection type

Plug-in connection

Functions

Overvoltage protection (Diode)

Short-circuit protection, outputs available

General

Admissible range

20.4 – 28.8 V (11.8 – 14.4 V), Power supply

Current consumption

250 mA, Internal current consumption (5 V DC), Outputs

Degree of protection

IP20

Number of channels

32, Output

Overvoltage category

II

Pollution degree

2

Protection

Protection class: 1

Repetition rate

1 s

Residual ripple

≤ 5 %

Type

Digital module

Used with

XC100/200 (expandable with up to 15 XI/OC modules)

Voltage type

DC

Ambient conditions, mechanical

Impact resistance

500 g/ 50 mm ±25 g

Shock resistance

15 g, Mechanical, Shock duration 11 ms

Vibration resistance

10 - 57 Hz, ± 0.075 mm

57 - 150 Hz ± 1.0 mm

Climatic environmental conditions

Ambient operating temperature - min

0 °C

Ambient operating temperature - max

55 °C

Ambient storage temperature - min

-25 °C

Ambient storage temperature - max

70 °C

Electro magnetic compatibility

Emitted interference

Class A (according to DIN/EN 55011/22)

Voltage dips

10 ms

Terminal capacities

Terminals

Optionally, screw terminals or spring-loaded terminals for digital/analog modules

Electrical rating

Leakage current

0.1 A

Power loss

Max. 1.25 W

Rated control supply voltage

External voltage for outputs/module (20 mA for module supply)

Us: 24 V DC (-15 %/+20 %)

Rated operational current (Ie)

3.2 A at AC-3, 230 V

0.2 A at DC-13, 110 V

Rated operational voltage

24 (12) V DC

Short-circuit protection

Yes, Outputs

8 A, Fuse, Outputs

Supply voltage at AC, 50 Hz - min

0 VAC

Supply voltage at AC, 50 Hz - max

0 VAC

Supply voltage at DC - min

20.4 VDC

Supply voltage at DC - max

28.8 VDC

Communication

Connection type

XIOC-TERM32 (connector and cable), Power supply

LED indicator

Status indication: 16 Green LED (switchable: 0 - 15, 16 - 31)

Input/Output

Delay time

1 ms typ., Outputs, Delay time from 1 to 0, Debounce OFF

0.3 ms, Outputs, Off -> On, Debounce OFF

Input current at signal 1

0 mA

Load current

Min. 1 mA

Number of inputs (digital)

0

Number of outputs (digital)

32

Output

Transistor (source type)

32 Outputs (24 V DC, 0.2 A)

Output current

0.2 A

Output voltage

24 V DC (-15 %/+20 %)

Safety

Explosion safety category for dust

None

Explosion safety category for gas

None

Potential isolation

Outputs: Opto-isolated

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

1.25 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Meets the product standard's requirements.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Brochures

eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf

Slice card modular I/O system for the machine building industry XN300 - brochure

Declarations of conformity

DA-DC-00003857.pdf

DA-DC-00003438.pdf

Drawings

eaton-electronic-devices-in-out-module-xioc-output-module-dimensions.eps

eaton-electronic-devices-dimensions-xioc-output-module-dimensions.eps

eaton-electronic-devices-local-inputoutput-xioc-output-module-3d-drawing.eps

eCAD model

DA-CE-ETN.XIOC-32DO

Manuals and user guides

MN05002002Z_EN

mCAD model

DA-CS-xioc

DA-CD-xioc



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia