

ZFH232-22

- **4 Contacts**
- **Metal enclosure**
- **single-pedal types**
- **Cable entry M 20 x 1.5**
- **High level of stability**
- **Low operating height of pedal**
- **Protective shield with wide opening**
- **Also available as safety foot switch**

Data

General data	
Product name	F 232
Standards	EN 60947-5-1 DIN VDE 0660-200 BG-GS-ET-15
Enclosure material	Aluminium
Enclosure coating material	powder-coated
Material of the cover	Aluminium
Material of the pedal	Glass-fibre, reinforced thermoplastic
Material of the protective shield	Aluminium
Colour of the housing	RAL 9006 (White aluminum)
Gross weight	1675.000 g
General data - Features	
Protective shield	Yes
Probing possible	Yes
Number of openers	2
Number of shutters	2
Mechanical data	
Mechanical life, minimum	1,000,000 Operations
Mechanical data - Connection technique	
Terminal Connector	Screw connection

Cable section, maximum	1 x 2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Width	170 mm
Height	189 mm
Depth	274 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Snap action

Pictures

Product picture (catalogue individual photo)



ID: ktfh-f01

| 337,6 kB | .jpg | 352.778 x 277.283 mm - 1000 x 786 Pixel - 72 dpi
| 30,0 kB | .png | 74.083 x 58.208 mm - 210 x 165 Pixel - 72 dpi

Dimensional drawing basic component



ID: ktf--g01

| 31,9 kB | .cdr |
| 5,5 kB | .png | 74.083 x 114.3 mm - 210 x 324 Pixel - 72 dpi
| 200,6 kB | .jpg | 352.425 x 544.689 mm - 999 x 1544 Pixel - 72 dpi

Dimensional drawing basic component



ID: 1tf--g01

| 89,6 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 Pixel - 72 dpi
| 33,0 kB | .cdr |
| 7,6 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

Dimensional drawing basic component



ID: 5tfh-g01

| 145,0 kB | .jpg | 352.778 x 285.044 mm - 1000 x 808 Pixel - 72 dpi
| 5,1 kB | .png | 74.083 x 59.972 mm - 210 x 170 Pixel - 72 dpi
| 42,1 kB | .cdr |

Diagram



ID: ktf--k02

| 17,4 kB | .cdr |