Specifications

Eaton 125419



Catalog Number: 125419

Eaton SPX Variable frequency drive, 400 V AC, 3-phase, 200 kW, IP54, Radio interference suppression filter, OLED display, FR10

General specifications

Product Name
Eaton SPX variable frequency drive

Catalog Number
125419

EAN
4015081230259

Product Length/Depth
602 mm

Product Height
2020 mm

Product Width
595 mm

Product Weight
275 kg

Certifications
CE
Safety: EN 61800-5-1: 2003
RCM
UL File No.: E134360
Certified by UL for use in Canada
CUL
DNV
Specification for general requirements: IEC/EN 61800-2
UL 508C
UL Category Control No.: NMMS, NMMS2, NMMS7. NMMS8
CSA-C22.2 No. 14
IEC/EN 61800-3
IEC/EN61800-5
CSA Class No.: 3211-06
IEC/EN61800-3
RoHS, ISO 9001
UL
UL report applies to both US and Canada

Powering Business Worldwide

General

Degree of protection

IP54

NEMA 12

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Fitted with:

Radio interference suppression filter

DC link choke

OLED display

Internal DC link

PC connection

Control unit

IGBT inverter

Frame size

FR10

Functions

4-quadrant operation possible

Mounting position

Vertical

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Suitable for

Branch circuits, (UL/CSA)

Climatic environmental conditions

Altitude

Above 1000 m with 1 % performance reduction per 100 m

Max. 3000 m

Max. 1000 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient operating temperature at 150% overload - min

-10 °C

Ambient operating temperature at 150% overload - max

50 °C

Ambient storage temperature - min

-40 °C

Climatic proofing

< 95 % relative humidity, no condensation, no corrosion, no dripping water

Main circuit

Mains voltage - min

380 V

Mains voltage - max

500 V

Operating mode

Optional: Vector control with feedback (CLV)

U/f control

Sensorless vector control (SLV)

Output frequency - min

0 Hz

Output frequency - max

320 Hz

Output voltage (U2)

400 V AC, 3-phase

500 V AC, 3-phase

480 V AC, 3-phase

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

460 A

Rated operational current (Ie) at 150% overload

385 A

Rated operational power at 380/400 V, 50 Hz, 3-phase

200 kW

Rated operational power at 380/400 V, 50 Hz, 3-phase, 110% overload

250 kW

Rated operational voltage

500 V AC, 3-phase

400 V AC, 3-phase

480 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Supply frequency

50/60 Hz

Switching frequency

3.6 kHz, 1 - 6 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

480 VAC

Motor rating

Assigned motor current IM at 400 V, 50 Hz, 110% overload

437 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

349 A

Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload

361 A

Assigned motor current IM at 440/480 V, 60 Hz, 110% overload

414 A

Assigned motor power at 460/480 V, 60 Hz, 3-phase

300 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase, 110 % overload

350 HP

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

6

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA)

Communication

Communication interface

PROFIBUS-DP

Modbus-TCP, optional

BACnet/IP, optional

LonWorks, optional

CANopen®, optional

Design verification

Equipment heat dissipation, current-dependent Pvid

5000 W

Heat dissipation capacity Pdiss

0 W

DeviceNet, optional

BACnet MS/TP, optional

EtherCAT, optional

Ethernet IP, optional

Modbus-RTU, optional

PROFINET, optional

Connection to SmartWire-DT

No

Protocol

LON

PROFIBUS

CAN

Data-Highway

TCP/IP

DeviceNet

Other bus systems

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

385 A

Static heat dissipation, non-current-dependent Pvs

0 W

Heat dissipation details

Operation (with 150 % overload)

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Connecting drives to generator supplies

Electromagnetic compatibility (EMC)

SPI - Variable frequency drives with a common DC bus

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004868.pdf

DA-DC-00004869.pdf

Drawings

eaton-frequency-inverter-spx-dimensions-013.eps

eaton-frequency-inverter-spx-dimensions.eps

Installation instructions

IL04020008Z

Multimedia

Eaton variable frequency drives - Demand more than good enough

Eaton variable frequency drives - Demand more innovation

Eaton variable frequency drives - Demand more expertise

How does a VFD work to save energy and money?

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.