Specifications

Eaton 102464



Catalog Number: 102464

Eaton xEnergy Basic LV systems Low voltage switchgear. Glass door, for HxW=2060x600mm, Clip-down handle, white

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	102464
EAN	**Product Length/Depth**
4015081023523	45 mm
Product Height	**Product Width**
2010 mm	615 mm
Product Weight	**Compliances**
7.3 kg	RoHS conform

Powering Business Worldwide

Product specifications

Special features

Can be used as left door for two-leaf versions
Transparent doors
Single wing door
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249)
Left door for two-section design with 1200 mm enclosure widths

Type

Additional equipment for floor-standing service distribution board
IVS

Features

Version as glazed door
EMC-version

Accessory/spare part type

Doors

Surface finishing

With powder coating
Powder coating

Color

White
Traffic white (RAL 9016)

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

2060 mm

Suitable for width

600 mm

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Cover/door color

Transparent

Cover/door type

Rotary lever

Material

Steel

Sheet steel/glass

Housing material

Sheet steel/glass

Model

Stop door

Mounting method

Floor standing distribution board

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia