EMPTY ENCLOSURE

# TK PS 1313-7-to



## TK PS 1313-7-to

**Empty enclosure**

**CUSTOMIZE**

130 x 130 x 75 mm
Article number: 11100501

Empty enclosure, Base: polystyrene, Grey, similar to RAL 7035, Cover: polycarbonate, transparent

without pre-embossings

IP66 IK07 690V AC 1000V DC

## Technical data

### Measures

| | |
|---|---|
| Width: | 130 mm |
| Length: | 130 mm |
| Height: | 75 mm |
| Inner height: | 63 mm |

### Material:

| | |
|---|---|
| Box: | Polystyrene, light grey, similar to RAL 7035 |
| Cover: | Polycarbonate, transparent |
| Sealing: | Polyurethane |
| Cover screw: | Polyamide 6, fiber-glass reinforced |
| material: | polystyrene |

## Accessory

| |
|---|
| ASS-kl - External hinge set |
| HBA - Mounting material |
| MPS-KRI - Mounting plate |
| NS 35-106 - Standard rail |
| NS 35-81 - Standard rail |
| TK ABL - External fixing lugs kit |
| TK DST - Spacing kit |
| TK MPI-1313 - Mounting plate |
| TS 15-111 - Standard rail |

### Environmental attributes

| | |
|---|---|
| Ambient temperature (min.): | -25 °C |
| Ambient temperature (max.): | 40 °C |
| Ambient temperature (24 h): | 35 °C |
| Max. rel. humidity at 25° C (short term): | 95% |
| Max. rel. humidity at 40° C: | 50% |

Created on 2018-07-26. No responsibility is taken for the correctness of this information. Improvements for technical progress reserved.

**Günther Spelsberg GmbH + Co. KG** · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299

EMPTY ENCLOSURE

# TK PS 1313-7-to

## Other attributes

| | |
|---|---|
| Ingress protection: | IP66 - acc. EN 60529 / DIN VDE 0470-1 |
| Impact resistance: | IK07 acc. DIN EN 5012 / VDE 0470 Part 100 |
| Protection class: | II - isolate protection acc. VDE 0106 |
| Rated insulation voltage AC: | 690 V |
| Rated insulation voltage DC: | 1000 V |
| Heavy metals-free: | Yes |
| PVC-free: | Yes |
| Silicone-free: | Yes |
| Fitted for outdoor application: | No |
| Combustion behaviour acc. to UL 94: | HB acc. UL94 |
| Combustion behaviour acc. to VDE: | 650°C acc. VDE 0471/ EN 60695 |
| sealable: | Yes |
| weatherproof: | No |
| Cable entries: | No |
| Cover screw torque: | 1.2 N m |
| Domed fastener torque: | 1.5 N m |
| External hinge torque: | 1.5 N m |


**Günther Spelsberg GmbH + Co. KG** · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299