Date: 11/04/2023

ERPP3/8"-PPU-L250/12-PP44A-5PVC

ERPP3/8"-PPU-L250/12-PP44A-5PVC

Item number: 48698015

Quantity: 1 pcs.

Order code: FLSPCMMZ1000MZM05HAZZ0200UZZZZZZZZZZZZZZZZNZZ
KBOCA02501ZZ

Overview:
ERPP3/8"-PPU-L250/12-PP44A-5PVC
Float Switch Type FLS-PF
Pressure: max. 3 bar
Temperature range: 0°C up to 60°C
Fluid density: 1000 kg/m³
Material: Polypropylene (PP)
Electrical connection: Cable PVC 5 m
Process connection: Mounting thread upwards 3/8"BSP
Switch function 1: Change-over (SPDT) 200 mm
Switch rating: max. AC 230V; 40VA; 1A / DC 230V; 20W; 0.5A
Float: Polypropylene PP44A; Float outer diameter: 44 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 250 mm

Details:
ERPP3/8"-PPU-L250/12-PP44A-5PVC
Float Switch Type FLS-PF
Pressure: max. 3 bar
Temperature range: 0°C up to 60°C
Fluid density: 1000 kg/m³
Material: Polypropylene (PP)
Electrical connection: Cable PVC 5 m
Process connection: Mounting thread upwards 3/8"BSP
Switch function 1: Change-over (SPDT) 200 mm
Switch rating: max. AC 230V; 40VA; 1A / DC 230V; 20W; 0.5A
Float: Polypropylene PP44A; Float outer diameter: 44 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 250 mm

© 2023 - WIKA Instruments s.a.r.l.