Rittal – The System.

Faster – better – everywhere.

# Polycarbonate enclosures PK without knockouts – PK 9518.100

Date : Apr 27, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# Polycarbonate enclosures PK without knockouts – PK 9518.100

created: 27.04.2021 build on www.rittal.com/uk-en



## Product description

| | |
|---|---|
| **Applications:** | Ambient temperature range: -35 °C...+80 °C<br>The specified temperatures may be limited by the installed equipment |
| **Material:** | Enclosure: Fibreglass-reinforced polycarbonate<br>Cover transparent: Polycarbonate, all-round foamed-in PU seal<br>Cover screws: Polyamide<br>Insulating bungs: Polyethylene |
| **Colour:** | RAL 7035 |
| **Protection category IP to IEC 60 529:** | IP 66 |
| **Protection category NEMA:** | NEMA 4X |
| **IK Code:** | IK08 |
| **Supply includes:** | Enclosure with cover<br>Cover screws<br>Insulating bungs for wall mounting screws |
| **Basic material:** | Polycarbonate |

## Product description

| | |
|---|---|
| **Dimensions:** | Width: 182 mm<br>Height: 180 mm<br>Depth: 111 mm |

| | |
|---|---|
| **Cover:** | transparent |
| **Ambient temperature range:** | -35 °C...+80 °C |
| **Packs of:** | 1 pc(s). |
| **Weight/pack:** | 0.66 kg |
| **EAN:** | 4028177139671 |
| **Customs tariff number:** | 94037000 |
| **ETIM 7.0:** | EC000261 |
| **ETIM 6.0:** | EC000261 |
| **eCl@ss 8.0/8.1:** | 27180101 |
| **eCl@ss 6.0/6.1:** | 27180101 |
| **Product description:** | PK Polycarbonate enclosure, WHD: 182x180x111 mm, fibreglass-reinforced polycarbonate, without knockouts, with transparent cover |

## Approvals

| | |
|---|---|
| **Approvals:** | C-UL<br>DNV-GL<br>UL |
| **Certificates:** | NA |
| **Declarations:** | Declaration of conformity |