
Blocks & Holders


French Ferrule Fuses

Modular fuse holders — CMS

New



- Indicator for fuse melts and/or striker (120/690V)
- Clip for rail mounting in two positions
- Cable size max. 35 mm²
- Provision for locking
- IP 20




J211056

CMS 14: Fuse 14x51
In max: 50A; Vn max: 690V

Poles	CATALOG NUMBER				REFERENCE NUMBER				N° Mod. (17.5 mm)	Packing
	Standard	+ Indicator	+ Microswitch	Micro + ind.	Standard	+ Indicator	+ Microswitch	Micro + ind.		
N	29000				N222468				1,5	6
1	29002	29004	29020	29120	F222990	M200778	K214645	N201837	1,5	6
1 + N	29010	29011			E201323	M201836			3	3
2	29012	29013	29021	29121	J211056	C211579	R215157	K211057	3	3
3	29014	29015	29024	29124	J212091	Z212611	T215665	D211580	4,5	2
3*			29025 *	29125 *			Y216681 *	K212092 *	6	1
3 + N	29016	29017	29026	29126	L213128	D213627	L217199	A212612	6	1
4	29019				G214136				6	1

* 2 microswitches



P217708

Unipolar fuse holder for accessories (**)

Function	CATALOG NUMBER	REFERENCE NUMBER	N° Mod. (17.5 mm)	Packing
Blown fuse, fuse presence, prebreaking	29030	P217708	1,5	6
Blown fuse only	29031	L223524	1,5	6

(**) Enables installation of accessory microswitch and/or indicator

Accessories (***)



M218741



F213629

Description	CATALOG NUMBER	REFERENCE NUMBER	N° Mod. (17.5 mm)	Packing
Micro Kit 1P	29051	M218741	1,5	1
Micro Block 3P	29052	C219261	4,5	1
Block 2 Micro 3P	29053	D219791	4,5	1
Micro assembly pins	29265	J214138		10
Micro enlargement pin	29264	F213629		10
Fuse holder assembly pins	29050	Z218223		10
Indicator	29054	-		1
Lock	29057	M223525		1

(***) See technical features for mounting information

Standards: IEC 269-2-1 / 947-3