


ARCALUB-X.CHAIN-PINION-08AB1-Z12-G

Chain lubrication pinion

Chain lubrication pinion simplex, Lubricant feed axial

Technical information



Your current product variant

Version	AB-/B-1	Chain lubrication pinions, simplex design

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website

Technical data

	Lubrication of chains	Usage
	Simplex (single-row)	Design
	axial	Lubricant feed
	Pinion: plastic, roller: open cell PU foam	Material
t_{op}	0 °C … +60 °C	Operating temperature
	7 m/s	Max. permissible circumferential speed at outside diameter
	Oil	Lubricant
	08 A/B-1	Chain type according to ISO 606
z	12	Teeth number
d	49.07 mm	Pitch circle diameter
d_a	53 mm	
d_b	39 mm	
B_1	29 mm	
B_2	5 mm	
L_1	30 mm	
L_2	41 mm	
L_3	55.5 mm	
L_4	71.2 mm	
W	15 mm	Width across flats
≈m	0.3 kg	Weight

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website