DATASHEET - BBA-TP4/300

Incoming set, 4p, 560A, to 300mm²

Part no. **BBA-TP4/300**
138385

Powering Business Worldwide

General specifications	
Product name	Eaton xEffect SASY 60i terminal plate
Part no.	BBA-TP4/300
EAN	4015081351657
Product Length/Depth	90 millimetre
Product height	260 millimetre
Product width	228 millimetre
Product weight	2.55 kilogram
Compliances	RoHS conform
Product Tradename	xEffect SASY 60i
Product Type	Busbar system component
Product Sub Type	Terminal plate
Delivery program	
Type	60 mm system Connection
Technical Data - Electrical	
Rated operation current (Ie)	560 A
Rated operational current	560 A
Rated operational current (Ie) - max	560 A
Creepage resistance	CTI 200
Technical Data - Mechanical	
Material	Silicon free, chlorine free
Busbar thickness - min	5 mm
Busbar thickness - max	10 mm
Busbar width - min	12 mm
Busbar width - max	30 mm
Terminal capacity (conductor)	95 mm² - 300 mm² MCM 300 - MCM 600
Conductor cross section - max	300 mm²
Width clamp	228 mm
Design verification as per IEC/EN 61439 - technical data	
Temperature resistance	Temperature resistant to 120 °C
Additional information	
Features	Self-extinguishing acc. UL 94
Functions	Connection kit Connections
Special features	Pole pitch adjustable Fixing direct over busbar terminals Including shroud with adjustable width Looping is possible
Suitable for	Round conductor connection Four-pole Sector conductor connection Strip conductor connection Flat rail
Used with	25 mm x 5/10 mm rail 30 mm x 5/10 mm rail 20 mm x 5/10 mm rail Double T profile Connection 60 mm system

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)

Electric engineering, automation, process control engineering / Terminal block systems and system components / Terminal block systems / Busbar terminal (ecl@ss13-27-25-01-16 [BAA025018])			
Busbar thickness		mm	5 - 10
Busbar width		mm	12 - 30
Suitable for			Flat rail
Width clamp		mm	228
Max. conductor cross section		mm^2	300
Max. rated operation current Ie		A	560
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			Yes
Suitable for strip conductor connection			Yes

© 04/2023 by Eaton Industries GmbH