Specifications

Eaton 266653



Catalog Number: 266653

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, on the left side, red, size 1

General specifications

Product Name
Eaton Moeller series NZM operating element

Catalog Number
266653

EAN
4015082666538

Product Length/Depth
190 mm

Product Height
100 mm

Product Width
100 mm

Product Weight
0.877 kg

Compliances
UL/CSA
IEC
RoHS conform

Certifications
UL (File No. E140305)
UL (Category Control Number DIHS)
CSA (File No. 22086)
CE marking
UL listed
CSA (Class No. 1437-01)
UL489
CSA certified
CSA-C22.2 No. 5-09
IEC60947

Powering Business Worldwide

Product specifications

Used with

N(S)1(-4)
NZM1(-4)
PN1(-4)

Type

Accessory
Main switch assembly kit for
side panel mounting

Special features

External warning
plate/designation label can
be clipped on.
For enhanced busbar tag
shroud on the incomer side,
please order IP2X protection
against contact with a finger.
Kit for use as a main switch

Features

Lockable
Actuation of the switch on the control panel side wall
Switch mounting on mounting plate
Red-yellow for emergency switching off

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM1

Drawings

eaton-circuit-breaker-switch-nzm-mccb-dimensions-012.eps

eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-004.eps

Installation instructions

eaton-side-wall-actuator-nzm1-xs-xzb-il01203006z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CS-nzm1_xs

DA-CD-nzm1_xs

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Red

Fitted with:

External warning plate/marking plate in German/English

NZM...-XV4 extension shaft

Extension shaft

Black and yellow lightning symbol

Door coupling rotary handle

Padlock

Frame

NZM1

Activation type

Actuation on the left

Suitable for

Switch disconnector

Power circuit breaker

Emergency stop

Cover/door type

Door interlock lockable in the 0 position using up to 3 padlocks on the handle

Degree of protection / NEMA enclosure type

IP66

4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia