DATASHEET - SPCT2-460/4

Plug-in surge arresters, 4p, 460VAC, 4x20kA

Part no. **SPCT2-460/4**
167611

General specifications	
Product name	Eaton Moeller series xPole - SPCT2 Surge protection device
Part no.	SPCT2-460/4
EAN	4015081641017
Product Length/Depth	85 millimetre
Product height	67 millimetre
Product width	70 millimetre
Product weight	0.433 kilogram
Compliances	RoHS conform
Product Tradename	xPole - SPCT2
Product Type	Surge protection device
Product Sub Type	None
Delivery program	
Application	Open areas Residential buildings Utility buildings
Type	Surge arrester
Technical Data - Electrical	
Voltage protection level	2.2 kV
Voltage protection level (L-N)	0 kV
Voltage protection level (N-PE)	0 kV
Nominal voltage at AC	460 V
Nominal voltage at DC	0 V
Continuous voltage at AC - max	460 V
Continuous voltage at DC - max	0 V
PV-voltage - max	0 V
Nominal discharge surge current (8/20)	20 kA
Discharge surge current (8/20) - max	40 kA
Short-circuit breaking capacity (ISCCR)	0 kA
Signalling at the device	Optic
Technical Data - Mechanical	
Frame	4 modular spacing
Mounting method	DIN rail (top hat rail) 35 mm
Number of conductors without earthing	4
Conductor cross section (flexible, fine-strand) - min	35 mm^2
Conductor cross section (flexible, fine-strand) - max	35 mm^2
Conductor cross section (solid, solid-strand) - min	25 mm^2
Conductor cross section (solid, solid-strand) - max	25 mm^2
Degree of protection	IP20
Additional information	
Features	Category type 2
System configuration type	TN-S TN-C-S Other TN IT

Technical data ETIM 9.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)	
Electric engineering, automation, process control engineering / Internal and external lightning protection / Lightning protection (other) / Lightning protection (other, not specified) (ecl@ss13-27-17-90-90 [AHE465002])	
System configuration DC	No

System configuration IT		Yes
System configuration TN		Yes
System configuration TN-C		No
System configuration TN-C-S		Yes
System configuration TN-S		Yes
System configuration TT		No
System configuration other		Yes
Number of conductors (without earthing)		4
Nominal discharge surge current (8/20)	kA	20
Max. discharge surge current (8/20)	kA	40
Nominal voltage AC	V	460
Nominal voltage DC	V	0
Max. continuous voltage AC	V	460
Max. continuous voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	2.2
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
Max. overcurrent protection device, parallel connection (fuse)	A	0
Max. overcurrent protection device, series connection (fuse)	A	125
Short-circuit breaking capacity (Isccr)	kA	0
Integrated short-circuit protection		No
Integrated short-circuit protection selective to fuse gG	A	0
Integrated backup fuse		No
Leakage-current free		No
Mounting method		DIN rail (top hat rail) 35 mm
Construction size		4 modular spacing
Max. conductor cross section solid (solid, stranded)	mm^2	25
Max. conductor cross section flexible (fine-strand)	mm^2	35
With remote signalling contact		No
Signalling at the device		Optical
Category type 2		Yes
Degree of protection (IP)		IP20

© 04/2023 by Eaton Industries GmbH