ADC04030R5

# Glazed door, 400x300

Electrical components can be viewed while the door is closed, which keeps unauthorized personnel out and maintains the ingress protection.



| CHARACTERISTICS | |
|---|---|
| Note | Table 1 |
| Height | 400 mm |
| Width | 300 mm |
| Viewing Area Height | 259 mm |
| Viewing Area Width | 143 mm |
| No Locks | 1 |

**Item no.:** ADC04030R5
**EAN no.:** 8713574124578

## Technical data

**Description:** To replace the standard door, it provides a clear view of the components installed inside the enclosure. The lock(s) are interchangeable with all nVent HOFFMAN's standard lock(s).

**Material:** 1.2 mm mild steel / 1.5 mm for enclosures with a height or width of 500 mm or greater / 2 mm for enclosures with a height or width of 800 mm or greater and 4 mm clear safety glass.

**Finish:** RAL 7035 structured powder coating.

**Protection:** Complies with IP 55 | TYPE 12, 13, IK 07.

**Pack quantity:** 1 door.

## Features

**Feature:** Glazed enclosure door for mild steel wall mounted enclosures.

**Advantage:** The glazed door allows the electrical components to be seen while the enclosure's door is closed.

**Benefit:** The user can monitor the status of the components without the need for opening the enclosure's door maintaining the ingress protection.