Rittal – The System.

Faster – better – everywhere.



PK 9514.050

Polycarbonate enclosures PK

State: 30/1/2023 (Source: rittal.com/in-en)

PK 9514.050 - Polycarbonate enclosures PK with knockouts

Wall-mounted enclosure of fibreglass-reinforced polycarbonate. Protection category IP 66. Covers feature quick-release fasteners for speedy maintenance. Self-extinguishing material for safety.

Features

Model No.	PK 9514.050
Applications	Ambient temperature range: -35 °C...+80 °C The specified temperatures may be limited by the installed equipment
Material	Enclosure: Fibreglass-reinforced polycarbonate Cover: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal Cover screws: Polyamide Insulating bungs: Polyethylene
Colour	RAL 7035
Supply includes	Enclosure with cover Cover screws Insulating bungs for wall mounting screws
Standard	NEMA 4X
Protection category to IEC 60 529	IP 66
IK Code	IK08
Dimensions	Width: 180 mm Height: 110 mm Depth: 90 mm
Cover version	grey
Cable entry (quantity x diameter)	M20 M20/M25 M32/M40

© Rittal 2023

Features

No. of metric knockouts	16 x M20 2 x M20/M25 2 x M32/M40
Operating temperature range	-35 °C...80 °C
Basic material	Polycarbonate
Packs of	2 pc(s).
Weight/pack	0.864 kg
Copper weight (kg per piece)	0
Customs tariff number	94037000
EAN	4028177490208
ETIM 7.0	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	C-UL DNV-GL GOST UL
Explanations	Declaration of conformity