Specifications

Eaton 248268

Catalog Number: 248268

Eaton Distribution parts. Penetration for neutral conductor with test connector, 63A, 50/60Hz, 1HP



General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	248268
EAN	**Product Length/Depth**
4015082482688	80 mm
Product Height	**Product Width**
65.5 mm	17.5 mm
Product Weight	**Compliances**
0.116 kg	RoHS conform

Powering Business Worldwide

Product specifications

Color

Gray

Insulation body material

Other

Connectable conductor cross section (fine strand) - max

25 mm²

Connectable conductor cross section (fine strand) - min

1 mm²

Connectable conductor cross section (fine-strand) with cable end sleeve - max

25 mm²

Connectable conductor cross section (fine-strand) with cable end sleeve - min

1 mm²

Connectable conductor cross section (multi-wired) - max

25 mm²

Connectable conductor cross section (multi-wired) - min

1 mm²

Connectable conductor cross section (solid-core) - max

25 mm²

Connectable conductor cross section (solid-core) - min

1 mm²

Mounting height - min

80 mm

Nominal current

63 A

Number of clamp positions per level

1

Number of levels

1

Operating temperature - max

40 °C

Operating temperature - min

-25 °C

Rated operational voltage (Ue) - max

230 V

Resources

Drawings

eaton-dimensions-mas-zd7-p63.jpg

Wiring diagrams

Zd7_P63

Width/grid dimension

175 mm

Suitable for conductor material

Copper

Mounting method

DIN rail (top hat rail) 35 mm

Connection position

Above

Electrical connection 1 type

Screw connection

Electrical connection 2 type

Other

Inflammability class of insulation material (UL 94)

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia