

Black boot for high hygienic requirement areas. The shaft protects against splashes.

jalas® CLEAN 1430

EN ISO 20345:2022 S2, HRO, CI, HI, FO

Learn more

HIGH SHAFT FOR ENHANCED HYGIENE

Water repellant and metal free black boot for high hygienic requirement work areas. The high shaft protects against splashes for enhanced hygiene. Very comfortable with padded boot shaft. Made of PU coated leather. Heat and oil resistant outsole and toe cap in light composite. By purchasing this product, you are supporting Leather Working Group certified tanneries.

CHARACTERISTICS

- Excellent grip
- Extra comfortable
- High level of protection
- Excellent shock absorption

FUNCTIONS

- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Ventilating insole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Padded boot shaft
- Water repellent

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, metal-free requirements for shoes, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Cleaning, fishing, fishing industry work, food handling, foodstuff handling, gardening, healthcare, high hygiene areas, kitchen work, laboratory work, sanitation, security- and police work, soil preparation

PRIMARY INDUSTRIES OF USE

Food processing, life science and electronics, horeca

SPECIFICATION

TYPE Safety footwear, Boots
CATEGORY Cat. II
FITTING Regular
COLLECTION Clean
UPPER MATERIAL PU-coated leather
TOECAP MATERIAL Composite
LINING MATERIAL Polyamide
INSOLE FX2 Pro-X
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
COLOUR Black
NET WEIGHT, (SIZE 42) 1.29 kg

COMPLIANCE

CE Cat. II

EAC

Information/UIS

EN ISO 20345:2022
S2, HRO, CI, HI, FO

FEATURES

- Oil-resistant outsole
- Composite toecap
- Water repellent
- Heat-resistant outsole
- Ergothan Shock Absorption System
- Anti-static properties
- ESD

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1430-35	6408487547287
36	3	4	5	1430-36	6408487547331
37	4	5	6	1430-37	6408487547386
38	5	5½	6½	1430-38	6408487547430
39	6	6½	7½	1430-39	6408487547485
40	6½	7½	8½	1430-40	6408487547539
41	7	8	9	1430-41	6408487547584
42	8	9	10	1430-42	6408487547638
43	9	9½	11	1430-43	6408487547683
44	10	10½	11½	1430-44	6408487547737
45	10½	11	12½	1430-45	6408487547782
46	11	12	13	1430-46	6408487547836
47	12	13	14	1430-47	6408487547881
48	13	13½	14½	1430-48	6408487547935

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.