



jalas® TEMPUS 5608

EN ISO 20345:2011 S1, P, SRC ASTM F2413-18 M/I/C SD 35 PR ASTM F3445-21 SR

Learn more

COMFORTABLE SAFETY SHOE WITH A MULTICOLORED OUTSOLE

Ventilated, sporty, and comfortable safety shoe with a multicolored outsole and advanced shock absorption with PORON XRD, protective toe cap and a soft and flexible nail penetration insert made of textile material. The well proven outsole has a very effective grip pattern and is made of a special nitrile rubber for high durability. The JALAS® Tempus shoes are ESD and antistatic certified to be used in ESD protected work environments.

CHARACTERISTICS

- Excellent shock absorption
- Excellent grip
- Perfect fit
- Extra comfortable
- Very breathable
- Extremely light

FUNCTIONS

- Double shock absorption zones
- Oil-resistant outsole
- Anti-static properties
- Ventilating insole
- Low weight
- Bellows tongue
- Conforms with IEC 61340-5-1 (ESD)
- Soft
- Ergonomically shaped

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Indoors, environments with risk for outsole penetration, dry environments, clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Narrow/Regular
COLLECTION Tempus
UPPER MATERIAL Microfiber, Textile
TOECAP MATERIAL Steel
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Pro Slim
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL EVA
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING Laces
COLOUR Multi-coloured, White
NET WEIGHT, (SIZE 42) 0.93 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

Information/UIS

EN ISO 20345:2011
S1, P, SRC

ASTM F2413-18
M/I/C
SD 35 PR

ASTM F3445-21
SR

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Oil-resistant outsole
- Steel toecap
- Nail protection in plasma-treated composite (PTC) textile

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	5608-35	6408487544569
36	3	4	5	5608-36	6408487544613
37	4	5	6	5608-37	6408487544668
38	5	5½	6½	5608-38	6408487544712
39	6	6½	7½	5608-39	6408487544767
40	6½	7½	8½	5608-40	6408487544811
41	7	8	9	5608-41	6408487544866
42	8	9	10	5608-42	6408487544910
43	9	9½	11	5608-43	6408487544965
44	10	10½	11½	5608-44	6408487545016
45	10½	11	12½	5608-45	6408487545061
46	11	12	13	5608-46	6408487545115
47	12	13	14	5608-47	6408487545160
48	13	13½	14½	5608-48	6408487545214

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.