Date: 22/04/2024

F2808 500 N ±0.15% Fnom 2.0 ±0.2 mV/V tension/compression

SPP-Tension-/compression force transducer, model F2808

Item number:	83800540
Quantity:	1 pcs.
Order code:	SPP-F2808-M2250C3A4K010300XXXXXXXXXXXXXXXXXXXX M1066FO5168
Overview:	F2808 500 N ±0.15% Fnom 2.0 ±0.2 mV/V tension/compression Model: F2808 Tension/compression force transducer, S-Typ, female thread Force direction: tension/compression Rated force/Rated load: 500 N Relative linearity error: ±0.15% Fnom Output signal: 2.0 ±0.2 mV/V Electrical connection: Cable output, free wires Cable length: 3 m Force transmission: M4 Ingress Protection IP: IP66 Technical data acc. to datasheet: FO51.68
Details:	SPP-Tension-/compression force transducer, model F2808 Technical data acc. to datasheet: FO51.68 Model: F2808 Tension-/compr. force transd., S-Type Miniature,female thread, 0..5N-0..2,000N Force direction: tension/compression Rated force/Rated load: 500 N Relative linearity error: ±0.15% Fnom Output signal: 2.0 ±0.2 mV/V Electrical connection: Cable output, free wires Cable length: 3 m Force transmission: M4 Ingress Protection IP: IP66

© 2024 - WIKA Instruments s.a.r.l.