

ABH 18-26 AS

Cordless rotary hammer drill

With SDS plus and an impact energy of 2.6 joules for drilling up to 26 mm in concrete.

Product number: 7 140 03 61 00 0

Details

- The powerful, brushless motor delivers 2.6 joules of impact energy and ensures rapid drilling progress as well as high chisel grinding capacity.
- Kickback monitoring with intelligent rapid shutdown should the hammer drill kick back suddenly for optimum user protection.
- Electronic Precision Control (EPC) slowly ramps up the working speed for perfect handling and control when working with sensitive materials and challenging surfaces.
- Simple and precise speed control using the throttle.
- Fatigue-free working thanks to compact design and few vibrations.
- Change the chisel position (Vario-Lock) – lock the chisel in 36 positions for the optimum working position every time.
- Bright working area thanks to integrated LED light.
- Clamps or hooks the bit if the drive to the drill spindle is interrupted.
- Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. “Electronic Cell Protection” (ECP) protects the battery from overload, overheating and total discharge.
- ProCORE Li-Ion battery with high-power cells, charge status indicator and “Electronic Cell Protection” (ECP). ECP protects against overload, overheating and total discharge.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- 1 handle
- 1 x tool cloth
- 1 depth stop
- 1 tool case (L-Boxx 136)

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Speed, no load	0 - 980 rpm
Impacts	0 - 4,350 rpm
Impact energy	2.6 J
Tool Holder	SDS-plus
Hole diameter, concrete	26 mm
Hole diameter, masonry	68 mm
Capacity in steel Ø	13 mm
Capacity in wood Ø	30 mm
Weight without storage battery	3.20 kg

Sound pressure level LpA Uncertainty of measured value KpA	88 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	99 dB 3 dB
Vibration value 1 αhv 3-way Vibration value 2 αhv 3-way	αh,D 15,2 m/s² αh,D 9,9 m/s²
Uncertainty of measured value Kα	1,5 m/s²

Application examples



Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.

