Date: 11/04/2023

TR34, 4...20mA, G1/4 fixed, 50 mm x 6 mm

TR34 Miniature resistance thermometer, explosion protected version, thread-mounted

Item number:	48783785		
Quantity:	1 pcs.		
Order code:	TR34-B-TT-CL0150-1160050-ZZZ-FZZ-ZZZ	R34	0061CW0000WIKA0Z

Overview:

TR34, 4...20mA, G1/4 fixed, 50 mm x 6 mm

ATEX / IECEx
Output signal: 4...20mA 0°C 150°C
Electrical connection: Circular connector, M12x1

Process connection: Fixed threaded hex bushing G1/4 B
Process temperature: -30 ... +150°C
Sensor diameter ød: 6 mm
Insertion length A: 50 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Pin assignment: 1+ (10..30VDC) und 3- (0V)
Transmitter damping: Standard

Specifications according to data sheet: TE 60.34

Details:

TR34 Miniature resistance thermometer, explosion protected version, thread-mounted

Specifications according to data sheet: TE 60.34
Electrical connection: Circular connector, M12x1
Approvals: ATEX / IECEx
Output signal: 4…20mA, 2-wire
Transmitter Unit: °C
Process temperature: -30 ... +150°C
Transmitter initial value: 0°C (Standard configuration)
Transmitter final value: 150°C (Standard configuration)
Process connection: Fixed threaded hex bushing G1/4 B
Sensor diameter ød: 6 mm
Insertion length A: 50 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Pin assignment: Standard pin connection 1+ (10..30VDC) and 3- (0V)
Transmitter damping: Standard

© 2023 - WIKA Instruments s.a.r.l.