Modular Signal Towers / KombiSIGN 72

# KS72 Classic BM 24VAC/DC GN/YE/RD



| | |
|---|---|
| **Part No.:** | **649.000.02** |
| **Series:** | **KombiSIGN 72** |

| **MECHANICAL DATA** | |
|---|---|
| Height | 212 mm |
| Diameter | 70 mm |
| Materials | PA-GF<br>PC |
| Dome colour | Green<br>Red<br>Yellow |
| Housing colour | Black |
| Protection category | IP65 |
| Connection | Spring-type terminal |
| cross-sectional area maximum | 1,50mm² / 16AWG |
| Cable entry | Through hole |
| Cable entry maximum | d = 11 mm |
| Tension relief | Not present |
| Type of fixing | Base mounting |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 398 g |
| Product weight | 353 g |

| **ELECTRICAL DATA** | |
|---|---|
| Operating voltage | 24V |
| Operating voltage type | AC/DC |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 240 mA |
| Rated inrush current | <500mA |
| Protection class | Protection class 2 |
| Pollution degree | 3 |


| **OPTICAL DATA** | |
|---|---|
| Light source | LED |
| Light colour | Green<br>Red<br>Yellow |
| Optical signal image | Permanent |
| Blink frequency (Hz) | 1 Hz |
| Service life optical | 50,000 h maximum |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Modular Signal Towers / KombiSIGN 72

# KS72 Classic BM 24VAC/DC GN/YE/RD

**DRAWING**




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.