Date: 11/04/2023

SA-11; 0 ... 1 bar; 4...20 mA, 2-W

Pressure transmitter for sanitary applications

Item number: 12472868

Quantity: 1 pcs.

Order code: SA-11-A-BBD-SE-AGA4ZZ-ZZZ W101Z-F2A-GSSAK6 LABEL-PG1DE-ZZZZZ- ZZZZZ

Overview:
SA-11; 0 ... 1 bar; 4...20 mA, 2-W
@ 10 ... 30 V DC; Accuracy: 0.5% of span
union nut DIN 11851 with conical coupling DN 50;
4-pin L-plug DIN EN 175301-803, IP65 UB=1, 0V=2
Specifications according to data sheet: PE 81.80
System fill fluid: KN 77 Synthetic oil

Label: WIKA standard without / with Tag-number

Details:
Pressure transmitter for sanitary applications
Model SA-11
Specifications according to data sheet: PE 81.80
Wetted parts: stainless steel 1.4435
Case: stainless steel
Permissible medium temperature: -20 ... +150 °C (-4 ... +302 °F)
Output signal: 4 ... 20 mA, 2-wire
Unit: bar
Measuring range: 0 ... 1 bar
Process connection: union nut DIN 11851 with conical coupling DN 50
Accuracy: 0.5% of span
Electrical connection: 4-pin L-plug DIN EN 175301-803, IP65
Power supply: 10 ... 30 V DC
Pin assignment: UB=1, 0V=2
Made in Germany on label
WIKA standard - specification according to data sheet
System fill fluid: KN 77 Synthetic oil
Import documentation CIS-States: without

Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.