Date: 11/04/2023

TW10-F FPW 1/2 NPT female U=120 mm B=0.260 inch (6.6 mm) SS316/316L

Flanged Thermowell TW10, solid machined

Item number:	48766236
Quantity:	1 pcs.
Order code:	TW10-F-A-M-AHDUD-N-0012000078G3G3DA02200160ZZ-ZZ 00191 Z00191ZZZZYQ1Z
Overview:	TW10-F FPW 1/2 NPT female U=120 mm B=0.260 inch (6.6 mm) SS316/316L Flange: 1 inch 600 lbs RFSF Connection to thermometer [N]: 1/2 NPT female Material: SS316/316L Flange material: SS316/316L Thermowell style: Tapered Head length [H]: 78 mm Insertion length [U]: 120 mm Bar diameter [Bd or F2]: 30 mm Root diameter [Q]: 22 mm Tip diameter [V or F3]: 16 mm Bore size [B or d1]: 0.260 inch (6.6 mm) Bore depth / stem length (US) [A]: 191 mm Specifications according to data sheet: TW 95.10
Details:	Flanged Thermowell TW10, solid machined Specifications according to data sheet: TW 95.10 Welding options: Full penetration welded Thermowell style: Tapered Unit of measure: Metric (mm) Flange size: ASME 1 inch Pressure rating: Class 600 Flange face: RFSF (Raise face smooth finish) Connection to thermometer [N]: 1/2 NPT female Pipe sched. /Intern. nozzle dia.: WIKA (Standard Germany) Insertion length [U]: 120 mm Head length [H]: 78 mm Flange material: Stainless steel 316/316L Material: Stainless steel 316/316L Bar diameter [Bd or F2]: 30 mm Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 22 mm Tip diameter [V or F3]: 16 mm Bore depth / stem length (US) [A]: 191 mm Tip thickness [Tt]: 0.250 inch (6.4 mm) Model: TW10

© 2023 - WIKA Instruments s.a.r.l.