reolink	Reolink Innovation Limited	NVS8
Picture		
	Product Name	8-Channel 12MP PoE Network Video Recorder
External Interfaces	**Video Out**	1 HDMI, 1 VGA
	Audio Port	1 audio out channel, RCA
	USB Ports	2 x USB 2.0
	Ethernet Ports	8 x RJ-45, 10/100 Mbps self-adaptive PoE Ethernet interface (for IP cameras)
		1 x RJ-45, 10/100/1000 Mbps self-adaptive (for LAN/WAN)
Video	**Video Input**	PoE IP Camera x 8
	Video Output	**HDMI:** 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
		VGA: 1920x1080, 1280x1024, 1280x720, 1024x768
Audio	**Audio Input**	Cameras with built-in MIC
Recording	**Video Compression**	H.265, H.264
	Live View/Playback	12MP/8MP/5MP/4MP/3MP/1080P/720P
	Synchronous Playback	1-4 channels (Supports only 1-channel playback if you view it in 8MP or higher resolution)
	Recording Modes	Person/Vehicle/Pet Detection, Motion-triggered Detection; 24/7 Recording
Storage	**Internal HDD**	1 SATA interface (2TB HDD included)
	External HDD	1 eSATA interface for HDD
	Max. Capacity	12TB (up to 6TB capacity for each HDD)
PoE	**Max. Power per Port**	25W
	Supported Standard	IEEE 802.3 af/at
Network	**Network Protocols**	HTTPS, TCP/IP, UDP, DHCP, P2P, UPNP, RTMP, SMTP, SSL/TLS, DNS, DDNS, NTP
	Browsers Supported	Edge, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; Smart phone: iOS, Android
	Max. User Access	20 Users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
General	**Power Supply**	DC 48V ~ 53V
	Power Consumption	<10W (without HDD & PoE)
	Working Environment	-10°C ~ + 45°C (14°F~113°F); 10% ~ 90%
	Dimensions	255 x 49 x 232mm
	Weight	1.4kg (without HDD)
Warranty	**Limited Warranty**	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.