7060 - COMPACT FLOW REGULATORS, EXHAUST, BSPP



maximum working pressure	10 bar 1 MPa 145 psi
working temperature	0 to 70 °C 32 to 158 °F 273 to 343 °K
adjustment screw	NICKEL PLATED BRASS
body	TECHNICAL POLYMER
sub-base	NICKEL PLATED BRASS
'O'-rings	NBR
gripping ring	STAINLESS STEEL
screw	NICKEL PLATED BRASS

inch Part numbers | Convert to inch | Convert to oz | Reset Filters

Part Nb	ØD (MM)	C	E (mm)	F (mm)	F1 (mm)	H (mm)	Hmaxi (mm)	H1 (mm)	L (mm)	L1 (mm)	ØT (mm)	(kg)
	All	All	All	All	All	All	All	All	All	All	All	All
7060 04 10	4	G1/8	5	10	16	38	44	16	22	9	10	.02
7060 06 10	6	G1/8	5	10	16	38	44	16	22	9	10	.02
7060 06 13	6	G1/4	5.5	10	16	36.5	42.5	15	22	9	10	.02
7060 08 10	8	G1/8	4.5	14	19	41.5	48	18	28	10.5	14	.032
7060 08 13	8	G1/4	5.5	14	19	41.5	48	18.5	28	10.5	14	.034
7060 08 17	8	G3/8	5.5	14	19	41.5	48	17	28	11	14	.034
7060 10 13	10	G1/4	5.5	17	23	45.5	53.5	20	31.5	12.5	17	.053
7060 10 17	10	G3/8	5.5	17	23	45.5	54	20	31.5	12.5	17	.054
7060 12 17	12	G3/8	5.5	17	23	45.5	54	20	35	12.5	17	.056
7060 12 21	12	G1/2	7.5	17	24	45.5	54	20	35	13	17	.058