Specifications

Eaton 199388

Catalog Number: 199388

Eaton DC1 Variable frequency drive, 230 V AC, 1-phase, 4.3 A, 0.37 kW, IP66/NEMA 4X, Radio interference suppression filter, 7-digital display assembly, Local controls, Additional PCB protection, UV resistant, FS1



General specifications

Product Name
Eaton DC1 Variable frequency drive

Catalog Number
199388

EAN
4015081977772

Product Length/Depth
162 mm

Product Height
232 mm

Product Width
161 mm

Product Weight
2.5 kg

Certifications
CUL
EAC
CE
UkrSEPRO
UL File No.: E172143
CE marking
IEC/EN 61800-2
IEC/EN 61800-3
UL 508C
IEC/EN 61800-5-1
UL Category Control No.: NMMS, NMMS7
UL
UL Listed
UL report applies to both US and Canada
RCM

Powering Business Worldwide

CSA-C22.2 No. 14
IEC/EN61800-5
R
Certified by UL for use in Canada

Features & Functions

Features

Parameterization: Fieldbus
Parameterization: drivesConnect
Parameterization: Keypad
Parameterization: drivesConnect mobile (App)

Fitted with:

Local controls
UV resistance
7-digital display assembly
PC connection
Radio interference suppression filter
Control unit
Additional PCB protection
IGBT inverter
Internal DC link

General

Cable length

75 m, unscreened, maximum permissible, Motor feeder
50 m, screened, maximum permissible, Motor feeder
C3 ≤ 25 m, maximum motor cable length
150 m, unscreened, with motor choke, maximum permissible, Motor feeder
C1 ≤ 1 m, maximum motor cable length
C2 ≤ 5 m, maximum motor cable length
100 m, screened, with motor choke, maximum permissible, Motor feeder

Communication interface

CANopen®, built in
OP-Bus (RS485), built in
SmartWire-DT, optional
Modbus RTU, built in

Connection to SmartWire-DT

No

Degree of protection

NEMA 4X
IP66

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Climatic environmental conditions

Altitude

Max. 4000 m
Above 1000 m with 1 % derating per 100 m

Ambient operating temperature - min

-20 °C

Ambient operating temperature - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

60 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Efficiency

97 % (η)

Input current ILN at 150% overload

Frame size

FS1

Mounting position

Vertical

Product category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Protocol

EtherNet/IP
MODBUS
CAN
Other bus systems

Radio interference class

C1: for conducted emissions only
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Suitable for

Branch circuits, (UL/CSA)

6 A

Leakage current at ground IPE - max

2.49 mA

Mains switch-on frequency

Maximum of one time every 30 seconds

Mains voltage - min

200 V

Mains voltage - max

240 V

Operating mode

U/f control
PM motors
Sensorless vector control (SLV)
BLDC motors
Synchronous reluctance motors
Speed control with slip compensation

Output frequency - min

0 Hz

Output frequency - max

500 Hz

Output voltage (U2)

230 V AC, single-phase
240 V AC, single-phase

Overload current IL at 150% overload

6.45 A

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

48 Hz

Rated frequency - max

62 Hz

Rated operational current (Ie)

4.3 A at 150% overload (at an operating frequency of 6 kHz and an ambient air temperature of +40 °C)

Rated operational voltage

230 V AC, 1-phase
240 V AC, 1-phase

Resolution

0.1 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

10 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

175 % IH

Supply frequency

50/60 Hz

Switching frequency

8 kHz, 4 - 32 kHz adjustable (audible), fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

240 V

Braking function

Braking torque

Max. 100 % of rated operational current Ie, variable, DC - Main circuit

Resources

Application notes

Operating Single Phase Motors

Dependency of the output current on switching frequency and ambient temperature

DX-COM-STICK3_Connection

Conformal Coating

The OP System Bus - Parameterizing - Control

Motor data - Motor Protection - V/f curves Slip Compensation

Motor rating

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

4.3 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

4.3 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

0.5 HP

Apparent power

Apparent power at 230 V

0.99 kVA

Apparent power at 240 V

1.03 kVA

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

4

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))

I/O Configuration

Low Temperature Applications

Operating Permanent Magnet and Brushless DC Motors

PI controller

Starting, Stopping and Operation

Fire Mode

Connecting drives to generator supplies

Update DX-COM-STICK3

Set Point Setting

How does the internal motor protection work?

Access to Parameter Levels 2 + 3 Parameter Lock - Load Default

Electromagnetic compatibility (EMC)

Brochures

eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf

DA-SW-drivesConnect

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004184.pdf

DA-DC-00003964.pdf

DA-DC-00004555.pdf

DA-DC-00004552.pdf

Drawings

eaton-frequency-inverter-dc1-dimensions.eps

Installation instructions

eaton-powerxl-dc1-ip66-single-phase-motors-instruction-leaflet-il040058zu.pdf

Installation videos

Video PowerXL DA1

PowerXL Variable Frequency Drives DC1 and DA1 - EN

Manuals and user guides

MN040003_EN

eaton-canopen-communication-manual-for-variable-frequency-drives-variable-speed-starters-da1-db1-dc1-de11-mn040019-en-us.pdf

MN040018_EN

MN040022_EN

MN040058_EN

mCAD model

e3_s1_ip66_mit_bedienelementen.stp

e3_s1_ip66_mit_bedienelementen.dwg

Multimedia

Looking for variable frequency drives DC1 and DA1 which can be used in harsh environments?

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia