K.HB 3/4" drive metric 6-point sockets



Standards:

NF ISO 2725-1, NF ISO 1711-1, ISO 2725-1, ISO 1711-1, DIN 3124, ASME B107.5

Description:

- OGV® profile: more powerful tightening, preserves fasteners.
- Secure attachment of plunger lock accessories
- Quick release button.
- Finish: satin chrome.

© FACOM 2020

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	Hex Size [mm]	Weight [g]	Colour []
K.19HB	19.0	36.0	30.1	51.0	14.0	6.0	207.0	Red 3020
K.21HB	21.0	36.0	32.0	51.0	14.0	6.0	208.0	Black 9004
K.22HB	22.0	36.0	33.4	51.0	14.0	6.0	221.0	
K.23HB	23.0	36.0	36.0	52.5	14.0	6.0	244.0	
K.24HB	24.0	36.0	36.0	52.5	16.0	6.0	237.0	Red 3020
K.26HB	26.0	36.0	38.9	52.5	16.0	6.0	231.0	Black 9004
K.27HB	27.0	36.0	39.7	52.5	18.0	6.0	232.0	Red 3020
K.28HB	28.0	36.0	41.0	52.5	18.0	6.0	239.0	Black 9004
K.29HB	29.0	36.0	42.0	52.5	18.0	6.0	245.0	Red 3020
K.30HB	30.0	36.0	43.2	59.0	20.0	6.0	282.0	Black 9004
K.32HB	32.0	36.0	45.9	59.0	22.0	6.0	301.0	Red 3020
K.33HB	33.0	36.0	48.1	59.0	22.0	6.0	330.0	Black 9004
K.34HB	34.0	36.0	48.4	59.0	24.0	6.0	322.0	Red 3020
K.35HB	35.0	36.0	50.1	59.0	24.0	6.0	344.0	Black 9004
K.36HB	36.0	36.0	51.0	59.0	24.0	6.0	347.0	Red 3020
K.38HB	38.0	40.0	54.3	66.9	27.0	6.0	478.0	Black 9004
K.40HB	40.0	40.0	56.0	66.9	27.0	6.0	493.0	
K.41HB	41.0	40.0	57.3	66.9	27.0	6.0	504.0	
K.42HB	42.0	40.0	59.5	66.9	27.0	6.0	552.0	
K.43HB	43.0	40.0	60.7	66.9	27.0	6.0	560.0	
K.44HB	44.0	40.0	61.9	66.9	28.0	6.0	587.0	
K.46HB	46.0	40.0	63.5	75.0	30.0	6.0	641.0	
K.50HB	50.0	40.0	68.5	75.0	33.0	6.0	725.0	

© FACOM 2020

K.54HB	54.0	45.0	74.0	75.0	36.0	6.0	880.0	
K.55HB	55.0	45.0	74.7	75.0	36.0	6.0	875.0	

© FACOM 2020