*Date: 11/04/2023*

# ERPP1/2"-PPU-L300/12-PP44A-3PVC

## ERPP1/2"-PPU-L300/12-PP44A-3PVC

Item number: 48747298

Quantity: 1 pcs.

Order code: FLSPCMNZ1000MZM03HBZZ0200UZZZZZZZZZZZZZZZZNZZ
KBOCA03001ZZ

Overview:
ERPP1/2"-PPU-L300/12-PP44A-3PVC
Float Switch Type FLS-PF
Pressure: max. 3 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Material: Polypropylene (PP)
Electrical connection: Cable PVC 3 m
Process connection: Mounting thread upwards 1/2"BSP
Switch function 1: Change-over (SPDT) 200 mm
Switch rating: max. AC 230V; 40VA; 1A / DC 230V; 20W; 0.5A
Float: Polypropylene PP44A; Float outer diameter: 44 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 300 mm

Details:
ERPP1/2"-PPU-L300/12-PP44A-3PVC
Float Switch Type FLS-PF
Pressure: max. 3 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Material: Polypropylene (PP)
Electrical connection: Cable PVC 3 m
Process connection: Mounting thread upwards 1/2"BSP
Switch function 1: Change-over (SPDT) 200 mm
Switch rating: max. AC 230V; 40VA; 1A / DC 230V; 20W; 0.5A
Float: Polypropylene PP44A; Float outer diameter: 44 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 300 mm

*© 2023 - WIKA Instruments s.a.r.l.*