Specifications

Eaton 121987

Catalog Number: 121987

Eaton Distribution parts. Phase busbar, 2-phase, 18qmm, pin, 1m, 2,5M/46



General specifications

Product Name
Eaton Distribution parts

Catalog Number
121987

EAN
4015081201877

Product Length/Depth
1009 mm

Product Height
37 mm

Product Width
22 mm

Product Weight
0.628 kg

Compliances
RoHS conform

Certifications
UL 508

Powering Business Worldwide

Product specifications

Used with

Busbar

BB-UL

Type

BB-UL

Busbar

Features

Insulated

Accessory/spare part type

Busbar for miniature circuit breaker

Electric connection type

Pin

Rated operational current for specified heat dissipation (In)

80 A

Rated surge voltage

10 KV

Rated uninterrupted current (Iu)

80 A

Static heat dissipation, non-current-dependent

0 W

Suitable for number of devices

46

Application

Switchgear for industrial and advanced commercial applications

Number of poles

Forty-six-pole

Color

Other

Rated short-time withstand current (Icw)

0 kA

Ambient operating temperature - max

100 °C

Ambient operating temperature - min

-5 °C

Cross section

Resources

Drawings

eaton-3d-drawing-140311-01.jpg

eaton-3d-drawing-140311-02.jpg

Installation instructions

MA150501419

System overview

eaton-explosion-drawing-140311.eps

18 mm²

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

0 W

Number of modular spacings

46

Number of phases

2

Pitch dimensions

0 mm

Rated operational voltage (Ue) - max

277 V

Rated conditional short-circuit current (Iq)

10 kA

Functions

Busbar

Suitable for

46 devices

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia