Separate units ø 22: Heads

IP 66
To be combined with a clip and electrical blocks (p. 48)
Equipped with a locking ring
Plastic black bezel
Conform to IEC 60947-5-1

Characteristics (p. 94)
Cross reference list (p. 311)

► MUSHROOM HEAD - NON ILLUMINATED (CONTINUED)

Ø 40 - STAY-PUT	Push-pull to reset	Cat. No.
 L22DD01		● Red ● Black	**L22DD01** **L22DD03**

Ø 40 - STAY-PUT	Key to reset	Cat. No.
 L22GM01		Supplied with 2 keys profile n° 455 ● Red	**L22GM01**

► EN 418/ISO 13850 EMERGENCY STOP - NON ILLUMINATED

Ø 32 EN 418/ISO 13850 - STAY-PUT	Push-pull	Cat. No.
 L22DQ01		Head position visible from the side with yellow collar Compliant with the requirements of emergency stop: IEC 60947-5-5 /EN 418/ISO 13850 ● Red	**L22DQ01**

Ø 32 EN 418/ISO 13850 - STAY-PUT	Key to reset	Cat. No.
 L22GQ01		Supplied with 2 keys profile n° 455 Head position visible from the side with yellow collar Compliant with the requirements of emergency stop: IEC 60947-5-5 /EN 418/ISO 13850 ● Red	L22GQ01

Catalogue No. in bold: normally in stock at distribution outlets