
multimec® 3C/3E






Technical Data:


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
  low temp: -40/+115ºC
  high temp:-40/+160ºC

STANDARD 3C


Dimensions (Through-hole)




PCB layout



Dimensions (SMD)




PCB layout




VARIABLE HEIGHTS 3E


Dimensions (Through-hole)




PCB layout



Dimensions (SMD)



PCB layout



HOW TO ORDER

3 C	☐	☐☐
Switch	**Mounting** **T** through-hole **S** surface mount	**L 6** low temp. white **L 9** low temp. black **H 9** high temp.

Standard versions:
3CTL6
3CTL9
3CTH9
3CSH9
3CSH9R (tape/reel)

3 E	☐	☐☐	-	☐☐.☐
Switch	**Mounting** **T** through-hole **S** surface mount	**L 9** low temp. **H 9** high temp.		**Standard overall height** **08.0** **09.5** **10.4** **11.0** **12.0** **15.0**

Standard versions:
3ETL9
3ETH9
3ESH9
3ESH9R

Custom heights:
3E is available in any height from 08.0 to 15.0 mm.
Min. order qty. for custom heights is 2.000 pcs. / A start-up charge will apply.

Ordering example: 3CTL6 and 3ETL9 - 09.5

mec a/s jan. 2003

mec · Industriparken 23 · P.o. Box 26 · DK-2750 Ballerup · Denmark
Tel.: +45 44 97 33 66 · Fax: +45 44 68 15 14 · Web: www.mec.dk. · E-mail: danmec@mec.dk