Date: 22/04/2023

732.14.160 2.5 bar 2 x G 1/2 female

Differential pressure gauge, multi purpose, with diaphragm element,

Item number: 48803857

Quantity: 1 pcs.

Order code: 732.14-ZZZF-HBG325Z-AD-UZZZASZZ-ZZZZZ 7B 3Z3DFZ-IZZZZZZ112ZZ
LABEL-PG1DE-ZZZZZ

Overview:
732.14.160 2.5 bar 2 x G 1/2 female
lower mount
PN 100 bar
Wetted parts: stainless-steel or NiCr-alloy (Inconel) & FPM
with zero adjustment at adjustable pointer
Ingress protection: IP 54
class 1.6
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Pressure Gauge Standard: International (standard Europe)
stop-pin at 6 o'clock
WIKA Serial number *...*
Label: WIKA standard without / with Tag-number

Details:
Differential pressure gauge, multi purpose, with diaphragm element,
high overpressure limit
Model: 732.14
Specifications according to data sheet: PM 07.13
Case: stainless steel
Bezel ring: stainless steel
Movement: stainless steel
Wetted parts: stainless-steel or NiCr-alloy (Inconel) & FPM
Case filling: without
Nominal size: 160 mm
Overpressure safety/working pressure max.: PN 100 bar
Scale range: 0...2.5 bar
Process connection: 2 x G 1/2 female
Connector location: lower mount
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Accuracy class: class 1.6
Case surface: bare
Ingress protection: IP 54
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*
stop pin on dial: at 6 o'clock

© 2023 - WIKA Instruments s.a.r.l.

with zero adjustment at adjustable pointer

© 2023 - WIKA Instruments s.a.r.l.