Specifications

Eaton 248291

Catalog Number: 248291

Eaton Distribution parts. Undervoltage release, 230 V, delayed 0, 4N/O, 1HP



General specifications

Product Name
Eaton Distribution parts

Catalog Number
248291

EAN
4015082482916

Product Length/Depth
80 mm

Product Height
65.5 mm

Product Width
17.5 mm

Product Weight
0.106 kg

Compliances
RoHS conform

Certifications
EN45545-2
IEC 61373

Powering Business Worldwide

Product specifications

Used with

Undervoltage releases

Accessory

Accessory for miniature circuit breaker

Type

Accessory

Accessory for miniature

circuit breaker

Application

Switchgear for industrial and advanced commercial applications

Accessory/spare part type

Undervoltage release

Mounting method

For fitting on left to: FAZ

Additional equipment required

Under voltage coil

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-5 °C

Assembly width

1 TE

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

1

Number of contacts (normally open contacts)

1

Number of poles at main contact unit - max

1

Number of switches (fault signal)

0

Voltage type

AC

Functions

Under voltage coil

Resources

Declarations of conformity

DA-DC-03_Z-USD

Drawings

eaton-3d-drawing-mont-usa.jpg

eaton-dimensions-mas-usa.eps

eCAD model

ETN.Z-USD_230.edz

Installation instructions

IL019152ZU

mCAD model

z_usd_230.dwg

z_usd_230.stp

Wiring diagrams

eaton-3d-drawing-montusa1.jpg

US

Device fitting

Universal

Rated operational voltage (Ue) - max

230 V

Rated switch current

0 A

Suitable for current of main contact unit - max

0 A

Tripping time

Delayed 0.4 s

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia