Date: 11/04/2023

S73.100/4, -30...+50°C, L1=450 mmx6mm,

Gas actuated thermometer, stainless steel series

Item number:	48779548
Quantity:	1 pcs.
Order code:	S73.100-CCB-4GD-B0450-ZZZ-Z-Z-HZZ-AHAZZZ G5 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ
Overview:	S73.100/4, -30...+50°C, L1=450 mmx6mm, G 1/2 B axial laminated safety glass Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: S73.100, nominal size 100, adjustable stem and dial Unit: °C Scale range: -30 °C ... +50 °C Connection design: 4, compression fitting, sliding on stem Process connection: G 1/2 B Stem diameter: 6 mm Insertion length L1: 450 mm Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: axial Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.