
620K | Security & Alarm Kit

Tempo® A Textron Company
Knowledge. Solutions. Success.

APPLICATIONS

To better satisfy industry requirements, we've combined the new Model PE620 Loop Verifier with the popular Model 200EP Inductive Amplifier in this convenient kit. Designed specifically for the security and alarm industry, the PE620 can be connected to a Normally Open or Normally Closed loop pair and provides a distinct audible tone when the alarm condition occurs.Both units fit comfortably in the rugged 700C Carrying Case made of durable woven polyester. 1-year warranty.



FEATURES

- Latching feature provides a simple method for identifying intermittent failures ("swingers") and confirming operation of switches at remote locations
- In the latching mode, the unit will catch the alarm condition and continue sounding until the tester is reset
- As a tone generator, the unit provides a traditional variable tone that can be applied using the 24" red and black test leads or a convenient 6-position modular plug
- Convenient magnetic back plate allows the PE620 to be mounted directly to the control panel cabinet or door

BENEFITS

- Battery operated (9V not included) and can be used on any wiring system including datacom, telecom, security/alarm, audio and CATV.
- Provides tone signaling, continuity testing and telephone line polarity indication combined with a modular breakout adapter
- Selectable tone outputs for identifying multiple cable runs
- Includes multiple connection options
- CE version available

Tempo® A Textron Company
Knowledge. Solutions. Success.

tel 800.642.2155 | tel 760.598.9800 | fax 760.598.5634 | www.tempo.textron.com

© 2003 Tempo Research Corporation - All rights reserved
ML-0092
Subject to change without notice