Date: 11/04/2023

F73.100/6.1, -200...+50°C, L1=variablex10mm,

Gas actuated thermometer, stainless steel series

Item number:	48801734
Quantity:	1 pcs.
Order code:	F73.100-CNA-6GD-EVARI-N01-2-Z-HZZ-ZZZZZZ G7 FZZZEVCZIWP-AZ1ZZZZZ2ZZZZ
Overview:	F73.100/6.1, -200...+50°C, L1=variablex10mm, G 1/2 B axial Panel mounting flange, stainless steel standard capillary stainless steel 1.4571 Capillary length: 1 m Stem length L: 100 mm laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.100, nominal size 100, with capillary Unit: °C Scale range: -200 °C ... +50 °C Connection design: 6.1, compression fitting, sliding on capillary Process connection: G 1/2 B Stem diameter: 10 mm Insertion length L1: variable Capillary: standard capillary stainless steel 1.4571 Capillary length: 1 m Design of case mounting: Panel mounting flange, stainless steel Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Stem length L: 100 mm Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: axial Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.