TEGERA®





TEGERA® INFINITY 8815

Learn more

OUR THINNEST NITRILE DIPPED CUT F

Dexterous cut resistant glove with highest cut level F, suitable for precision work. Ultra light thanks to 18 gg knitted with CRF® Omni cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS

- Highest level of protection
- Good fingertip sensitivity
- Good grip
- Extra comfortable
- Flexible
- Durable

FUNCTIONS

- Withstands contact heat up to 100°C
- Soft
- Thin
- Approved for handling foodstuffs
- Reinforcement between index finger and thumb

CRF® omni

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Engineering, metalwork, paper industry work, repair work, sheet-metal work

PRIMARY INDUSTRIES OF USE

Pulp and paper, metal fabrication, machinery and equipment, mro, automotive, transportation

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves
CATEGORY Cat. II
COLLECTION Infinity
LINING MATERIAL 18 gg, CRF® Omni Technology, HPPE, Nylon, Spandex
LENGTH 220-270 mm
DEXTERITY 5
GRIP DESIGN Foam grip pattern
COLOUR Black
PAIRS PER: BUNDLE/CARTON 6/120
DISPLAY TYPE Bulk pack
DIPPING Palm-dipped
DIPPING MATERIAL Nitrile foam, Waterbased PU
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
CUT RESISTANCE (EN ISO 13997) Cut resistance level F
CUT RESISTANCE (EN ISO 13997) TDM: 31.2 N
INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Tungsten fibre thread, Elastane
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE

Cat. II

TP TC 019:2011

Information/UIS

EN 407:2004
X1XXXX

EN 388:2016
4X43F

EN 420:2003
+A1:2009

ANSI A6 CUT

ANSI 4 ABR

OEKO TEX® STANDARD 100 SE 14-214 RISE www.oeko-tex.com

ORIGINAL 04 EXCELLENT 2019 dermatest® dermatest-guarantee.de

Contact heat rating valid for palm area only

FEATURES

Cut protection

SIZE		ARTICLE NUMBER	EAN
6	XS	8815-6	7340118370965
7	S	8815-7	7340118371054
8	M	8815-8	7340118371146
9	L	8815-9	7340118371238
10	XL	8815-10	7340118371320
11	XXL	8815-11	7340118371412

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.