# 700-323-1BH01




## Input / Output module digital for 300

### 8x IN / 8x OUT

- Digital inputs and outputs

## Info

Digital mix modules for the 300 series

The module has 8 inputs and 8 outputs.

# Technical data

| | |
|---|---|
| **General information** | |
| Order number | 700-323-1BH01 |
| Article name | DEA 300, DC 24 V, 0.5 A, 8 inputs (DC 24 V)/8 outputs (DC 24 V, 0.5 A) |
| Scope of delivery | DEA 300, DC 24 V, 0.5 A, 8 inputs (DC 24 V)/8 outputs (DC 24 V, 0.5 A) |
| Dimensions (DxWxH) | 116 x 40 x 125 mm |
| Weight | Approx. 220g |
| Number of inputs | 8 |
| Number of outputs | 8 |
| Rated value | 0.5 A |
| Short-circuit protection | Electronic |
| Inductive cutoff voltage limit | -48 V |
| Power dissipation (nominal operation) | typ. 3.5 W |
| Front connectors | 20-pin |
| **Input voltage** | |
| For signal "0" | -3 ... +5 V |
| For signal "1" | +13 ... +30 V |
| Rated value | 24 V DC |
| Input current for signal "1" | typ. 7 mA |
| Delay time | 1.2 ... 4.8 ms |
| Can accommodate 2-wire initiator | Yes |
| **Cable length** | |
| Unshielded | 600 m |
| Shielded | 1000 m |
| **Electrical isolation** | |
| from the backplane bus | Yes (optocoupler) |
| in groups to | 8 |
| **Supply voltage UP, US** | |
| Rated value | 24 V DC |
| Ripple USS | max. 3.6 V |
| Permissible range (with ripple) | +20 ... +30 V |
| **Current draw** | |
| Internal (backplane bus) | typ. 55 mA |
| External (from +24 V/L+) | Max. 60 mA |
| **Ambient conditions** | |
| Ambient temperature | 0 °C ... +60 °C |
| Transport and storage temperature | -25 °C ... +75 °C |
| Pollution degree | 2 |
| Protection rating | IP20 |
| Approvals | CE |