



jalas® RESPIRO 3700R

EN ISO 20345:2011 S2, SRB

Learn more

Toecap material aluminium, PU midsole, plastic shank, TPU outsole, upper material nubuck leather;PU-coated leather;Textile

CHARACTERISTICS

- Excellent shock absorption
- Good grip
- Perfect fit
- Extra comfortable
- Very breathable

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Stabilizator
- Water repellent
- Polstered shaft edge
- Conforms with IEC 61340-5-1 (ESD)
- Double shock absorption zones
- Ultra-high air permeability, three-layer laminate, 'provided by IQTEX based on patented technologies'
- Perforated
- Perforated front section

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, dry environments, clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
FITTING Regular
COLLECTION Respiro
UPPER MATERIAL PU-coated leather, Nubuck leather, Textile
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Climate
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL TPU outsole
FASTENING Laces
COLOUR Black, Red, Blue
NET WEIGHT, (SIZE 42) 0.97 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN ISO 20345:2011 S2, SRB

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Water repellent
- Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	3700R-36	6408487504631
37	4	5	6	3700R-37	6408487504648
38	5	5½	6½	3700R-38	6408487504655
39	6	6½	7½	3700R-39	6408487504662
40	6½	7½	8½	3700R-40	6408487504679
41	7	8	9	3700R-41	6408487504686
42	8	9	10	3700R-42	6408487504693
43	9	9½	11	3700R-43	6408487504709
44	10	10½	11½	3700R-44	6408487504716
45	10½	11	12½	3700R-45	6408487504723
46	11	12	13	3700R-46	6408487504730
47	12	13	14	3700R-47	6408487504747

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.