SMALL-SCALE DISTRIBUTORS

AK 28 Plus



AK 28 Plus

Small-scale distributors

CUSTOMIZE

315 x 600 x 155 mm
Article number: 73362801

Distribution board - Industrial Quality - 2-row, 28 distribution units, 150 mm rail spacing, integrated ventilation elements to reduce the formation of condensate water, elastic entries on top, masking and labelling strips, additional double-membrane seals and other accessories

with additional connection space, with 35 mm standard rails, without PE/N terminal rails

Technical data

Measures

Width:	315 mm
Length:	600 mm
Height:	155 mm
Inner height:	95 mm
Inner width:	295 mm
Inner length:	580 mm

Material:

Box:	Polycarbonate
Cover:	Polycarbonate
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced
material:	Polycarbonate
Hinged window:	Polycarbonate,

Highlights

Reliable - The high protection class (IP65) and the robust, halogen-free design ensure reliable operation even in a tough industrial environment.

Certificates

Accessory

- AK3 KBL - Cable cover with document compartment
- AK3 TW - Partition wall
- AK3 NS35-14 - Standard rail
- AK3 NS35-275 - Standard rail
- AK3 ABL-ES - External fixing lugs
- AK3 STD - Schuko mounting socket
- AK3 KS M50 - Combination cable gland

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299

SMALL-SCALE DISTRIBUTORS

AK 28 Plus

	transparent

Other attributes

Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
Impact resistance:	IK08
Tackable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Color:	Grey
Rated insulation voltage AC:	1000 V
Rated insulation voltage DC:	1500 V
sealable:	Yes
Functional integrity:	none
Number of distribution units:	28
EMC design:	No
with lock:	No

AK AS - Masking off strips
AK AS-v - Masking off strips
AK SGA-1 - Lock fittings
AK SGA-2 - Lock fittings
KLS N 35 - Terminal block
KLS PE 35 - Terminal block
KST M25-33 - Combi connector
AK 14 PEN-SL - Terminal rails
AK 28 PEN-SL - Terminal rails

Environmental attributes

Ambient temperature (min.):	-35 °C
Ambient temperature (max.):	80 °C
Ambient temperature (24 h):	60 °C
Max. rel. humidity at 25° C (short term):	90%
Max. rel. humidity at 40° C:	50%

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299